



Final Report
Stormwater Management Report

3400 Dufferin Street & 8 Jane Osler Boulevard, City of Toronto



Prepared for Dufferin – 401 Properties Limited & Collecdev Inc.
by IBI Group
IBI Group Project #139570
August 9, 2022

Document Control Page

CLIENT:	Dufferin – 401 Properties Limited & Collecdev Inc.
PROJECT NAME:	3400 Dufferin Street & 8 Jane Osler Boulevard, City of Toronto
REPORT TITLE:	Stormwater Management Report
IBI REFERENCE:	IBI Group Project #139570
VERSION:	1
DIGITAL MASTER:	139570 3400 Dufferin Street_City of Toronto - Internal Documents\6.0 Technical\6.04 Civil\03 Reports\Revision 1\SWM
ORIGINATOR:	Shirley Beaudoin, CAD Technologist, Land Engineering
REVIEWER:	Neil Short, Director, Sr. Practice Lead, Land Engineering
AUTHORIZATION:	Jason Jenkins, P.Eng., P.E., Associate Manager, Land Engineering
HISTORY:	Identification Date Description of Issued and/or Revision
	SWM, August 09, 2022, 1st Submission (ZBA, SPA, & Plan of Subdivision)

AUTHORIZED FOR ISSUE BY:

IBI GROUP



Jason Jenkins, P.Eng., P.E.
 Associate Manager
 Land Engineering

Table of Contents

1	Introduction	1
1.1	Background	1
1.2	Existing Site Description	1
1.3	Site Proposal	2
1.4	Service Connections	2
2	Terms of Reference and Methodology	3
2.1	Terms of Reference	3
2.2	Methodology: Stormwater Management	3
3	Stormwater Management	4
3.1	Pre-Development Conditions	4
3.2	Grading	4
3.3	Allowable Release Rate	5
3.4	Quantity Control	5
3.5	Quality Control	7
3.6	Water Balance	9
3.7	Municipal Storm Sewers	12
3.8	Storm Service Connection	12
3.9	Emergency Overflow	13
3.10	Erosion and Sediment Control	13
4	Conclusions and Recommendations	14

List of Tables

Table 3.1	Allowable Release Rates	5
Table 3.2	Quantity Control Summary	6
Table 3.3	TSS Performance: Building A	7
Table 3.4	TSS Performance: Building B	7
Table 3.5	TSS Performance: Building C	7
Table 3.6	TSS Performance	8
Table 3.7	Water Balance Targets (Overall Subdivision)	9
Table 3.8	Initial Abstraction: Municipal ROW	9

Table 3.9	Water Balance Targets (Overall Subdivision, Adjusted).....	10
Table 3.10	Initial Abstraction: Block B.....	10
Table 3.11	Initial Abstraction: Block D.....	11
Table 3.12	Initial Abstraction: Block E.....	11
Table 3.13	Storm Sewer Performance	12
Table 3.14	Storm Service Performance	12

List of Figures

FIG 1	Aerial Plan	Following Report
-------	-------------------	------------------

List of Drawings

Draft Plan of Subdivision Drawing Set.....	Appendix C
Site Plan Application Drawing Set	Appendix C

Appendices

Appendix A Background Information

Appendix B Stormwater Analysis

Appendix C Engineering Plans

1 Introduction

1.1 Background

IBI Group Professional Services (Canada) Inc. (IBI Group) has been retained by Dufferin – 401 Properties Limited & Collecdev Inc. (the “Owner”) to prepare a Stormwater Management Report (SWM Report) to support the Draft Plan of Subdivision, Zoning By-Law Amendment (ZBA), and Site Plan Application (SPA) processes for a proposed mixed-use development located at 3400 Dufferin Street & 8 Jane Osler Boulevard (the “Subject Site”), in the City of Toronto (the “City”). The purpose of this report is to provide a municipal servicing strategy for storm drainage and stormwater management. More specifically, the report will evaluate Stormwater Management (SWM) opportunities and constraints, including:

- Calculate allowable and proposed runoff rates for the development;
- Evaluate suitable methods for attenuation and treatment of stormwater runoff; and
- Develop on-site control measures and examine theoretical performance to satisfy the City’s Wet Weather Flow Management Guidelines (WWFMG).

The following documents have been obtained from various sources:

- City of Toronto plan and profile drawings for Dufferin Street and Jane Osler Boulevard;
- City of Toronto Public Utilities Coordinating Committee (TPUCC) mapping;
- Grading and Servicing plans for 3450 Dufferin Street prepared by Schaeffer & Associates Ltd. (Schaeffer’s), dated July 2021;
- Dufferin Street Avenue Study Infrastructure Master Plan prepared by Fabian Papa and Partners, dated November 2014;
- Topographic Survey prepared by KRCMAR Surveyors Ltd., dated June 2022;
- Functional Road Design prepared by BA Group, dated July 2022; and,
- Architectural plans and site statistics prepared by gh3 Architects.

1.2 Existing Site Description

Located at 3400 Dufferin Street & 8 Jane Osler Boulevard in the City of Toronto at postal code M6A 2V1, the 1.668 ha subject site is bounded by Dufferin Street to the east, several single family dwellings and Jane Osler Boulevard to the south, an existing commercial building to the west, and 3450 Dufferin Street to the north which is currently under construction. Please see **Figure 1** following the report for an aerial view of the site.

It should be noted that a separate development application has been submitted by others for 3450 Dufferin Street which includes (2) new municipal road dedications immediately north of the subject site; Street A (North) and Street B (North). This will be discussed in greater detail in subsequent sections. Sample site plan drawings for the adjacent development application can be found in **Appendix A** for reference.

The site currently hosts an existing commercial building and an asphalt parking surface. The site is relatively flat with ground surface elevations ranging from 190.6 m to 189.2 m and is self-contained with a small external drainage area along the southern limit.

The subject site is located within the Basement Flooding Study Area (BFA) #16 which was completed in 2012, and the Dufferin Street Avenue Study which was completed in 2014. Excerpt copies of each study can be found within the appendices of this report.

1.3 Site Proposal

The proposed development includes the division of the site into various blocks as follows:

- Block A: 1,825 m² municipal road to be dedicated to the City as a new 23 m public road (Street A) which shall align with Street A (North) at 3450 Dufferin Street and continue to Dufferin Street within Block F of the development.
- Block B: 4,046 m² mixed-use block consisting of a 29-storey building (Building A) with (2) levels of underground parking.
- Block C: 1,049 m² municipal road to be dedicated to the City as a new 18.5 m public road (Street B) which shall align with Street B (North) at 3450 Dufferin Street and connect to Street A within Block F of the development.
- Block D: 4,079 m² mixed-use block consisting of a 29-storey building (Building B) with (2) levels of underground parking.
- Block E: 1,811 m² mixed-use block consisting of a 10-storey building (Building C) with (2) levels of underground parking.
- Block F: 3,870 m² municipal road to be dedicated to the City as a new 23 m public road (Street A) which shall connect Street A (North) to Dufferin Street.

In summary, Blocks A, C, and F shall be dedicated to the City as new municipal rights-of-way (ROW), and Blocks B, D, and E shall be developed as mixed-use blocks. Sample architectural drawings and the functional road design can be found in **Appendix A** for reference.

1.4 Service Connections

While a development site can typically share a single storm service connection, individual sanitary and domestic services are required for each built form to satisfy City's servicing policy. Accordingly, each building shall be serviced independently.

Furthermore, the Ontario Building Code (OBC) requires two fire service connections separated by an isolation value for any building above 84 m in height. As Building A and Building B exceed this threshold, a secondary fire service will be required for each. The following represents the number of service connections for each development block:

- Block B (Building A): (1) storm, (1) sanitary, (2) fire, and (1) domestic service;
- Block D (Building B): (1) storm, (1) sanitary, (2) fire, and (1) domestic service; and,
- Block E (Building C): (1) storm, (1) sanitary, (1) fire, and (1) domestic service.

Site servicing requirements will be discussed in greater detail in subsequent sections.

2 Terms of Reference and Methodology

2.1 Terms of Reference

The terms of reference used for the scope of this report have been based on the City of Toronto Design Criteria for Sewers and Watermains, dated January 2021, the City of Toronto Wet Weather Flow Management Guidelines, dated November 2006, and the Dufferin Street Avenue Study Infrastructure Master Plan, dated November 2014.

2.2 Methodology: Stormwater Management

As the proposed development has a total site area less than 5.0 ha (Table 7, Section 2, WWFMG), the following SWM criteria shall apply:

Quantity Control

Per the WWFMG, the allowable release rate to the municipal storm sewer system from the development site during a 2-year design storm event must not exceed the peak runoff rate from the site under pre-development conditions during the same storm event, the existing capacity of the receiving storm sewer, and per the Dufferin Street Avenue Study the allowable release rate shall be limited to 75 L/s/ha, whichever is more restrictive.

A maximum runoff coefficient of 0.5 shall be used in calculating the pre-development peak runoff. An overland flow route (major system) shall be provided within the developed site to direct runoff in excess of the 100-year storm to an approved overland flow outlet.

Quality Control

Long-term average removal of 80% of the total suspended solids (TSS) on an annual loading basis must be achieved. TSS removal efficiency is to be based on 100% of the runoff leaving the site from all storm events that occurs in an average year.

Water Balance

The criteria provided in the City's WWFMG outlines that controls should be in place, such that the runoff resulting from a 5 mm rainfall event must be retained on-site for rainwater re-use, infiltration, and/or evapotranspiration.

3 Stormwater Management

3.1 Pre-Development Conditions

Local storm infrastructure consists of:

- A 600 mm storm sewer within Dufferin Street, which conveys flows in a southerly direction; and,
- A 600 mm storm sewer within Jane Osler Boulevard which conveys flows in a westerly direction.

As previously mentioned, (2) new municipal roads are proposed immediately north of the subject site as part of a separate development application, which will include various storm infrastructure. As the proposed storm infrastructure within the adjacent development has not been sized to accommodate flows from the subject site, it shall not be considered as a suitable outlet for the subject site.

The site currently hosts an existing building and a surface asphalt parking lot resulting in a pre-development runoff coefficient in excess of 0.50, however as the WWFMG limits the allowable release rate using a pre-development runoff coefficient of 0.50, this shall govern.

3.2 Grading

Under pre-development conditions, the rear yards of the adjacent residential lots fronting Jane Osler Boulevard drain to the subject site. This external area will be taken into consideration as part of the overall stormwater management strategy.

Emergency overland flow route in excess of a 100-year storm is directed to both Jane Osler Boulevard and Dufferin Street under pre-development conditions. Existing drainage patterns shall be maintained wherever feasible. Please refer to drainage area plans **STM-1** and **STM-2**.

3.3 Allowable Release Rate

As previously mentioned, per the WWFMG the allowable release rate for each development block and the overall subdivision is the 2-year pre-development flow, calculated using the City's IDF data and a maximum runoff coefficient of 0.50 and per the Dufferin Street Avenue Study release rates in the area must be further controlled to 75 L/s/ha. This is summarized in the following table.

Table 3.1 Allowable Release Rates

CATCHMENT	AREA (ha)	PER WWFMG (L/s)	PER AVENUE STUDY (L/s)
Municipal ROW	0.6641	81.3	49.8
Block B (Building A)	0.4046	49.6	30.3
Block D (Building B)	0.4002	49.0	30.0
Block E (Building C)	0.1652	20.2	12.4
Total Subdivision (Less Dufferin Widening)	1.634	200.2	122.6

As shown above, the post-development release rate for the subdivision shall be limited per the Dufferin Street Avenue Study to 122.6 L/s, as this is the more conservative rate. Please see the associated pre-development drainage area plan **STM-1** as part of the subdivision package.

3.4 Quantity Control

As previously mentioned, the post-development release rate for the subject site shall be limited to 75 L/s/ha per the Dufferin Street Avenue Study, which has been calculated to be **122.6 L/s**. Each block will require on-site underground storage and an orifice control. The 100-year peak orifice discharge for each block has been calculated using the following orifice discharge equation:

$$Q_{\text{Orifice}} = K \times A \times \sqrt{2 \times g \times h}$$

Block B (Building A)

To attenuate flows, a stormwater management tank with a minimum storage area of 95.0 m² and a 95 mm orifice plate shall be installed within the P1 level. Limiting the 100-year storage depth at 1.80 m the attenuated orifice discharge is calculated as follows:

$$Q_{\text{Block B}} = (0.63) \times \frac{\pi \times (0.095)^2}{4} \times \sqrt{2 \times 9.81 \times (1.80 - 0.095/2)} \times \frac{1000 \text{ L}}{1 \text{ m}^3} = 26.2 \text{ L/s}$$

Block D (Building B)

To attenuate flows, a stormwater management tank with a minimum storage area of 87.0 m² and a 95 mm orifice plate shall be installed within the P1 level. Limiting the 100-year storage depth at 1.44 m the attenuated orifice discharge is calculated as follows:

$$Q_{\text{Block D}} = (0.63) \times \frac{\pi \times (0.095)^2}{4} \times \sqrt{2 \times 9.81 \times (1.44 - 0.095/2)} \times \frac{1000 \text{ L}}{1 \text{ m}^3} = 23.3 \text{ L/s}$$

Block E (Building C)

To attenuate flows, a stormwater management tank with a minimum storage area of 53.0 m² and a 75 mm orifice plate shall be installed within the P1 level. Limiting the 100-year storage depth at 0.88 m the attenuated orifice discharge is calculated as follows:

$$Q_{\text{Block E}} = (0.63) \times \frac{\pi \times (0.075)^2}{4} \times \sqrt{2 \times 9.81 \times (0.88 - 0.075/2)} \times \frac{1000 \text{ L}}{1 \text{ m}^3} = 11.3 \text{ L/s}$$

Overall Subdivision

A 165 m length of 1,200 mm storm sewer and 200 mm orifice tube shall be installed within the new municipal roadways to attenuate flows for the subdivision, including flows from the external drainage area to the south. Limiting the 100-year storage depth at 1.21 m the attenuated orifice discharge is calculated as follows:

$$Q_{\text{subdivision}} = (0.82) \times \frac{\pi \times (0.200)^2}{4} \times \sqrt{2 \times 9.81 \times (1.21 - 0.200/2)} \times \frac{1000 \text{ L}}{1 \text{ m}^3} = 120.1 \text{ L/s}$$

The following is a summary of the stormwater management parameters pertaining to quantity control:

Table 3.2 Quantity Control Summary

CATCHMENT	STORAGE REQ'D (m ³)	STORAGE PROVIDED (m ³)	ALLOWABLE RELEASE RATE (L/s)	ORIFICE RELEASE RATE (L/s)	UN-CONTROLLED FLOW (L/s)	TOTAL RELEASE RATE (L/s)
Block B	117.4	134.9	30.3	26.2	0.0	26.2
Block D	112.6	168.4	30.0	23.3	0.0	23.3
Block E	46.8	105.4	12.4	11.3	0.0	11.3
Subdivision	192.1	197.9	122.6	120.1	0.0	120.1

As shown above, the total peak flow from the subdivision is calculated to be 120.1 L/s which is less than the allowable release rate of 122.6 L/s. By providing on-site storage and an orifice control for each development block and the municipal ROW, the City’s objectives for quantity control have been met. Please see detailed calculations which can be found in **Appendix B**.

It should be noted that regular inspection and maintenance of any storage element and orifice control should be conducted on a regular basis to ensure that the system is functioning as designed.

3.5 Quality Control

As previously mentioned, 80% TSS removal is required in order to meet the City’s WWFMG’s. The following discusses the water quality strategies for each block and the new municipal road.

Private Development Blocks

Based on the proposed site conditions and surface treatment, the following tables summarize each development block’s inferred TSS removal rate:

Table 3.3 TSS Performance: Building A

SURFACE TYPE	AREA (m ²)	EFFECTIVE TSS REMOVAL	OVERALL TSS REMOVAL
Conv. Roof	1,387	80	27.4
Intensive Green Roof	1,088	80	21.5
Landscape	0	80	0.0
Landscape over P1	225	80	4.4
Permeable Pavers	0	80	0.0
Impervious	1,346	0	0.0
TOTAL	4,046		53.4

Table 3.4 TSS Performance: Building B

SURFACE TYPE	AREA (m ²)	EFFECTIVE TSS REMOVAL	OVERALL TSS REMOVAL
Conv. Roof	1,399	80	27.4
Intensive Green Roof	1,026	80	20.1
Landscape	0	80	0.0
Landscape over P1	571	80	11.4
Permeable Pavers	0	80	0.0
Impervious	1,006	0	0.0
TOTAL	4,002		59.9

Table 3.5 TSS Performance: Building C

SURFACE TYPE	AREA (m ²)	EFFECTIVE TSS REMOVAL	OVERALL TSS REMOVAL
Conv. Roof	672	80	29.7
Intensive Green Roof	362	80	16.0
Landscape	0	80	0.0
Landscape over P1	183	80	8.9
Permeable Pavers	0	80	0.0
Impervious	435	0	0.0
TOTAL	1,652		58.9

Left untreated, each block will not achieve the City's requirement for 80% TSS removal. Therefore, it is proposed that a Stormfilter© system complete with media cartridges be installed for each block. All “dirty” areas within the drive aisle shall first be directed to the Contech chamber, whereas all other areas can be considered clean and routed directly to the stormwater management tank. Please refer to the Contech Sizing Report which can be found in **Appendix B**.

The Stormfilter© system is accepted as a standalone off-line treatment unit and meets the City of Toronto's criteria for 80% TSS per the WWMFG's. Any proposed substitutions will require approval from both the engineer of record and the City of Toronto.

It is recommended that the Stormfilter© system be inspected on a regular basis to ensure proper operation. Per Contech's recommendations, inspection and maintenance should be carried out at a minimal interval of 12 months with inspections prior to each winter season with filter replacements as required.

Municipal Right-of-Way

Based on the proposed site conditions and surface treatment, the following table summarizes the municipal ROW's inferred TSS removal rate:

Table 3.6 TSS Performance

SURFACE TYPE	AREA (m ²)	EFFECTIVE TSS REMOVAL	OVERALL TSS REMOVAL
Landscape	1,771	80	21.3
Impervious	4,870	0	0.0
TOTAL	6,641		21.3

As shown above, the new municipal roadway will not satisfy the City's criteria for quality control due to the high percentage of impervious surface. It is therefore proposed that a Contech CDS© 5-C oil-grit separator (OGS) (or approved equal) be installed downstream of the orifice control. By installing a City approved quality control unit, the City's requirements for quality control have been satisfied. Please see **Appendix B** for the detailed design sheet and OGS specification.

It should be noted that regular inspection and maintenance of any water quality control device should be conducted on a regular basis to ensure that the system is functioning as designed.

By adding City-approved stormwater quality treatment units for each development block and the municipal ROW, the City requirements for quality control (i.e. minimum 80% TSS removal) have been satisfied.

3.6 Water Balance

As required by the City’s TGS Tier 1, a rainfall depth of 5 mm must be retained over the entire area of development. In order to achieve the required volume, a combination of initial abstraction and water re-use will be incorporated. The following discusses the water balance targets for the overall subdivision and each development block independently.

Overall Subdivision

The water balance targets for the subdivision are summarized as follows:

Table 3.7 Water Balance Targets (Overall Subdivision)

CATCHMENT	AREA (m ²)	DEPTH (mm)	TOTAL REQUIRED VOLUME (m ³)
Municipal ROW	6,641	5.0	33.2
Block B (Building A)	4,046	5.0	20.2
Block D (Building B)	4,002	5.0	20.0
Block E (Building C)	1,652	5.0	8.3
Subdivision	16,341	--	81.7

New Municipal Roadways

As Blocks A, C, and F are to be dedicated to the City as new municipal roadways, a rainfall depth of 5 mm must be retained over the total area to be dedicated.

Based on initial abstraction values for each surface type, the total abstraction is calculated as follows:

Table 3.8 Initial Abstraction: Municipal ROW

AREA	AREA (m ²)	INITIAL ABSTRACTION	TOTAL (m ³)
Landscape	1,771	5	8.9
Impervious	4,870	1	4.9
TOTAL	6,641		13.7

As shown above, the new municipal roadways will be short of meeting the required water balance volume by 19.5 m³ (33.2 m³ – 13.7 m³) and will only achieve an aggregate depth of 2.1 mm. It is therefore proposed that each private development block (Blocks B, D, and E) be required to compensate for this shortfall on a pro-rated basis.

Overall Subdivision (Adjusted)

The following table summarizes the adjusted water balance targets for each development block.

Table 3.9 Water Balance Targets (Overall Subdivision, Adjusted)

CATCHMENT	AREA (m ²)	DEPTH (mm)	TOTAL REQUIRED VOLUME (m ³)
Municipal ROW	6,641	2.1	13.7
Block B (Building A)	4,046	7.0	28.4
Block D (Building B)	4,002	7.0	28.0
Block E (Building C)	1,652	7.0	11.6
Subdivision	16,341	--	68.0

As shown above, each private development block shall retain an additional 2.0 mm to compensate for the new municipal roadway. Please see **Appendix B** for the detailed design calculations.

Block B (Building A)

With an area of 4,046 m² and an adjusted water balance target of 7.0 mm, the corresponding water balance volume to be retained on-site is calculated to be **28.4 m³**. Based on initial abstraction values for each surface type, the total abstraction is calculated as follows:

Table 3.10 Initial Abstraction: Block B

AREA	AREA (m ²)	INITIAL ABSTRACTION	TOTAL (m ³)
Conv. Roof	1,387	1	1.4
Intensive Green Roof	1,088	7	7.6
Landscape	0	5	0.0
Landscape over P1	225	5	1.1
Permeable Pavers	0	5	0.0
Impervious	1,346	1	1.3
TOTAL	4,046		11.5

As shown above, 11.5 m³ is retained on-site through initial abstraction. The balance of 16.9 m³ will be retained through water re-use purposes such as landscape irrigation and / or toilet flushing. Confirmation from the irrigation and mechanical consultants shall be provided in a future submission. An adequate sump within the stormwater management tank will be provided within the P1 level to retain the total water re-use volume. Please see **Appendix B** for the detailed design sheet and detailed drawing **SS-01**.

Block D (Building B)

With an area of 4,002 m² and an adjusted water balance target of 7.0 mm, the corresponding water balance volume to be retained on-site is calculated to be **28.0 m³**. Based on initial abstraction values for each surface type, the total abstraction is calculated as follows:

Table 3.11 Initial Abstraction: Block D

AREA	AREA (m ²)	INITIAL ABSTRACTION	TOTAL (m ³)
Conv. Roof	1,399	1	1.4
Intensive Green Roof	1,026	7	7.2
Landscape	0	5	0.0
Landscape over P1	571	5	2.9
Permeable Pavers	0	5	0.0
Impervious	1,006	1	1.0
TOTAL	4,002		12.4

As shown above, 12.4 m³ is retained on-site through initial abstraction. The balance of 15.6 m³ will be retained through water re-use purposes such as landscape irrigation and / or toilet flushing. Confirmation from the irrigation and mechanical consultants shall be provided in a future submission. An adequate sump within the stormwater management tank will be provided within the P1 level to retain the total water re-use volume. Please see **Appendix B** for the detailed design sheet and detailed drawing **SS-01**.

Block E (Building C)

With an area of 1,652 m² and an adjusted water balance target of 7.0 mm, the corresponding water balance volume to be retained on-site is calculated to be **11.6 m³**. Based on initial abstraction values for each surface type, the total abstraction is calculated as follows:

Table 3.12 Initial Abstraction: Block E

AREA	AREA (m ²)	INITIAL ABSTRACTION	TOTAL (m ³)
Conv. Roof	672	1	0.7
Intensive Green Roof	362	7	2.5
Landscape	0	5	0.0
Landscape over P1	183	5	0.9
Permeable Pavers	0	5	0.0
Impervious	435	1	0.4
TOTAL	1,652		4.6

As shown above, 4.6 m³ is retained on-site through initial abstraction. The balance of 7.0 m³ will be retained through water re-use purposes such as landscape irrigation and / or toilet flushing. Confirmation from the irrigation and mechanical consultants shall be provided in a future submission. An adequate sump within the stormwater management tank will be provided within the P1 level to retain the total water re-use volume. Please see **Appendix B** for the detailed design sheet and detailed drawing **SS-01**.

3.7 Municipal Storm Sewers

As previously mentioned, it is proposed that a new 1,200 mm concrete storm sewer at a 0.20% slope be installed within Street A to provide storage specifically for the municipal ROW for stormwater attenuation. The storage element shall be connected to an oil-grit separator with a 1.0 m length of 200 mm PVC storm sewer (orifice control) and a 2.8 m length of 450 mm storm sewer at a 0.50% slope. The oil-grit separator shall be connected to the existing 600 mm storm sewer within Dufferin Street with a 17.3 m length of 450 mm PVC storm sewer installed at a 0.50% slope.

The following table illustrates the peak flow and corresponding capacity of the proposed storm sewer:

Table 3.13 Storm Sewer Performance

FROM	TO	STORM SEWER SIZE (mm)	SEWER SLOPE	PEAK FLOW (L/s)	CAPACITY (L/s)	PERCENT OF FULL FLOW
MH7 (OGS)	MH8	450	0.50%	120.1	201.60	60%

As shown above, the proposed storm sewer can easily convey its respective storm flow while operating at 60% of full flow capacity. Please refer to the detailed design calculations which can be found in **Appendix B**, and the design drawings **SS-01** and **SS-02**.

3.8 Storm Service Connection

It is proposed that each block be connected to the proposed municipal storm sewer with a PVC storm service. The following table illustrates the peak flow and corresponding capacity of each service:

Table 3.14 Storm Service Performance

BLOCK	FROM	TO	STORM SERVICE SIZE (mm)	SERVICE SLOPE	PEAK FLOW (L/s)	CAPACITY (L/s)	PERCENT OF FULL FLOW
Block B (Building A)	Ctrl MH1	1,200 mm (Street A)	200	2.0 %	26.2	46.4	56%
Block D (Building B)	Ctrl MH2	MH6 (Street A)	200	2.0%	23.3	46.4	50%
Block E (Building C)	Ctrl MH3	1,200 mm (Street A)	200	2.0%	11.3	46.4	24%

As shown above, the proposed storm service connections can easily convey the controlled discharge from each block while operating at 56% (or less) of full flow capacity. Please refer to the detailed design calculations which can be found in **Appendix B**, and the design drawings **SS-01** and **SS-02**.

3.9 Emergency Overflow

It is recommended that rooftop scuppers be installed to ensure emergency overflow from roof areas should rooftop drains become plugged.

All areas at grade level have been designed with positive drainage (away from the building).

Each stormwater management tank shall be designed with an emergency outlet to allow storm flows to spill to the adjacent municipal right-of-way in an emergency situation.

Maximum ponding within the development site shall not exceed City requirements of 0.30 m.

3.10 Erosion and Sediment Control

It is recommended that a sediment control fence per T-219.130-1 be installed along the perimeter of the site as required during demolition activities. All existing and proposed catch basins within close proximity of the subject site shall be protected with a geotextile fabric. A mud mat shall be installed as required to minimize distribution of mud into the public realm.

4 Conclusions and Recommendations

Quantity Control

By incorporating stormwater storage and an orifice control, each block shall be attenuated on-site and released to the municipal storm sewer within the new municipal roadways at an appropriate discharge rate. By incorporating stormwater storage (oversize pipe) and an orifice control within the new municipal roadway, the new municipal roadway will meet the City's target for quantity control.

Quality Control

By adding a water quality unit within each private development block and an oil-grit separator within the new municipal roadway, the overall subdivision will meet the City's target for quality control.

Water Balance

While the new municipal roadway will fall short of meeting the City's water balance target, Development Blocks B, D, and E will overcompensate for this shortfall. Through initial abstraction and graywater re-use (irrigation and toilet flushing), the overall subdivision will meet the City's target for water balance.

Summary

In summary, it can be concluded that the Zoning By-Law Amendment, Draft Plan of Subdivision application, and Site Plan application can be supported from both a storm servicing and a stormwater management perspective.



HIGHWAY 401


BRIDGELAND AVENUE

DEVELOPMENT SITE

DUFFERIN STREET

JANE OSLER BOULEVARD

CARTWRIGHT AVENUE

<p>CLIENT</p> <p>DUFFERIN - 401 PROPERTIES LIMITED & COLLECDEV INC.</p>	<p>PROJECT NAME</p> <p>3400 DUFFERIN STREET & 8 JANE OSLER BOULEVARD</p>		 <p>IBI GROUP Unit 300 – 8133 Warden Avenue Markham ON L6G 1B3 Canada tel 905 763 2322 fax 905 763 9983 ibigroup.com</p>		
	<p>SCALE:</p> <p>NTS</p>	<p>DATE:</p> <p>2022-06-20</p>	<p>FIGURE NAME</p> <p>AERIAL PLAN</p>	<p>FIGURE NO.</p> <p>FIG.1</p>	<p>REVISION</p> <p>1</p>
	<p>PROJECT ENG:</p> <p>JMJ</p>	<p>DRAWN BY:</p> <p>SB</p>			
	<p>CHECKED BY:</p> <p>JMJ</p>	<p>APPROVED BY:</p> <p>JMJ</p>			
	<p>PROJECT NO:</p> <p>139570</p>				

Appendix A

Background Information

Plan and Profile Drawings (City of Toronto)

TPUCC Mapping (City of Toronto)

Excerpt Dufferin Street Avenue Study (Fabian Papa & Partners)

Topographic Survey (KRCMR)



3450 Dufferin Site Grading and Servicing Plans (Schaeffer's)

Sample Architectural Drawings (gh3)

Functional Road Design (BA Group)

Subsurface Utility Engineering Study (Urban X)


JANE OSLER BOULEVARD



GRID NO.	NORTHING	EASTING
251	4942514.200	328201.200

SUBJECT SITE

- NOTE:
1. REPLACE AND RELOCATE EXISTING CATCH BASIN LEADS TO PROPOSED STORM SEWER, 250 mm DIA FOR SINGLE CATCH BASIN LEAD AND 300 mm DIA FOR DOUBLE CATCH BASIN LEAD.
 2. CONNECT PROPOSED CATCH BASIN TO THE PROPOSED STORM SEWER, 250 mm DIA LEAD FOR SINGLE CATCH BASIN AND 300 mm DIA LEAD FOR DOUBLE CATCH BASIN.
 3. ENCROACHMENT WITHIN BOULEVARD IS NOT PERMITTED WITHOUT PRIOR APPROVAL FROM THE CITY. IN CASE WHERE HEAVY EQUIPMENT HAS TO ENCROACH SOFT SURFACE BETWEEN CURBS AND THE EXISTING TREE, TREE PROTECTION ZONE (TPZ) HAS TO BE PROTECTED WITH STEEL PLATING AND MULCH AGAINST SOIL COMPACTION AND ROOT DAMAGE. TREE TRUNK TO BE PROTECTED WITH TRUNK FENCE. SEE SPECIFICATIONS FOR DETAILS.
 4. ANY SPEED BUMPS THAT ARE IMPACTED DURING CONSTRUCTION MUST BE REINSTATED TO EXISTING OR BETTER CONDITIONS.



EXISTING GROUND ELEVATION	175.00	175.50	176.00	176.50	177.00	177.50	178.00	EXISTING GROUND ELEVATION
STATION								

THESE AS-BUILT DOCUMENTS HAVE BEEN PREPARED BASED ON THE INFORMATION PROVIDED BY OTHERS. THE DESIGN PROFESSIONAL HAS NOT VERIFIED THE ACCURACY AND/OR THE COMPLETION OF THE INFORMATION AND SHALL NOT BE RESPONSIBLE FOR ANY ERRORS OR OMISSIONS WHICH MAY BE INCORPORATED HEREIN AS A RESULT.

AS-BUILT DRAWING

CH2M HILL
CONSULTANTS

NOTE:
ORIGINAL SEAL WITH PRESENTE
DATED 03/07/2014

JANE OSLER BOULEVARD
FROM WEST OF DUFFERIN STREET
STORM SEWER SEWER RE-CONSTRUCTION

DESIGN	P.K.	DRAWN	A.O.	CHECKED	N.P.	CONTRACT NO.	54FS-03VP	
SCALE	HORIZONTAL 1/200		VERTICAL 1/100		DRAWING NUMBER	U-5907-001		
DATE	FEBRUARY 15, 2014						SHEET	10 OF 11




Toronto Engineering and Construction Services

TED BROWNE, P. ENG.
ACTING DIRECTOR
ENGINEERING AND
CONSTRUCTION SERVICES
MANAGEMENT

NANCY BONHAM, P. ENG.
ACTING DIRECTOR
CONSTRUCTION SERVICES
CAPITAL WORKS DELIVERY

NO.	DATE	REVISIONS	INITIAL	SIGNED
1	07-26-2010	AS-BUILT DRAWING PREPARED BY CH2M HILL CANADA LTD.		
		REVISIONS PROVIDED BY THE CITY.		
		STORM SEWERS CONSTRUCTED IN 2015.		

DESCRIPTION	DATE
SURVEY (2013)	x1327460.dwg
DESIGN	x1327460.dwg
CITY	x1327460.dwg
DRAWING	x1327460.dwg
STREET LINE	x1327460.dwg





CUMAP (CITY UTILITY MAPPING)

DATA SETS
 WATER MAIN
 STORM SEWER
 SANITARY SEWER
 COMBINED SEWER



RELEASE AND INDEMNIFICATION AGREEMENT
 FOR THE USE OF CITY OF TORONTO DIGITAL SEWER \ WATER MAPPING

In consideration of the City of Toronto, hereinafter called the City, providing the above data (the "Data") to CompaName, (the "Applicant"), the Applicant hereby releases, remises and forever discharges the City, its successors and assigns from and of all manner of actions, causes of actions, debts, claims and demands whatsoever which against the said City, its successors or assigns the Applicant ever had or which the Applicant's heirs, executors, administrators, or assigns or any of them hereafter can, shall or may have for or by reason of the use or otherwise of the Data provided by the City to the Applicant and the Applicant will from time to time hereafter well and truly defend, save harmless and fully indemnify the City, its successors and assigns from and against all claims and demands which may be brought against or made upon the City, its successors or assigns and against all loss, cost and damage which the City, its successors or assigns may sustain, suffer or be put to in any way incidental to providing the Data to the Applicant.

The Data is protected by copyright of which the City is the sole owner. The applicant acknowledges and agrees that the Applicant is granted only a non-exclusive, restricted license to use the Data for the Applicant's own educational purposes. Neither the Applicant nor any of its Representatives may reproduce, modify or alter the Data by any means for any purpose other than the Applicant's own educational purposes, without the prior written consent of the City. Except as expressly permitted herein, the Data, or any portion of the Data, shall not be sold, licensed or otherwise transferred by the Applicant or any of its Representatives to any third parties either voluntarily or by operation of law. This agreement may not be assigned by the Applicant without the prior written consent of the City, which shall not be unreasonably withheld.

The Applicant acknowledges and agrees that the City makes no warranties with respect to the Data provided under this agreement as to content, completeness, accuracy, merchantable quality, or fitness for a particular purpose, express or implied, or acting by law or by statute, or by usage of trade or course of dealing. The entire risk as to the results and performance of the City's data is assumed by the Applicant and the City, its successors and assigns shall have no liability for reliance placed upon the Data by the Applicant or any other person or entity.



Dufferin Street Avenue Study

Infrastructure Master Plan

FINAL REPORT

November 2014



216 Chrislea Road, Suite 501 | Woodbridge, Ontario | L4L 8S5

Tel: 905-264-2420 | www.fabianpapa.com

Contents

Executive Summary	i
Contents	iv
Introduction	1
Purpose	1
Study Area	1
Class EA Master Plan Process	2
Problem/Opportunity Statement	2
Description of the Project Area	4
Demographics & Local Context	4
Land Use	4
Natural Environment	5
Socio-Economic Environment	8
Cultural Heritage	8
Existing Infrastructure	9
Future Conditions	13
Evaluation of Alternatives	15
Alternatives	15
Evaluation Methodology	16
Water Distribution	17
Design Criteria	17
Alternatives	19
Assessment & Evaluation of Alternatives	19
Preferred Solution	20
Implementation Considerations	20
Sanitary Sewerage	21
Design Criteria	21
Alternatives	22
Assessment & Evaluation of Alternatives	23
Preferred Solution	24
Implementation Considerations	32
Storm Drainage & Stormwater Management (SWM)	35
Stormwater Management Objectives	35
Alternatives	37
Assessment & Evaluation of Alternatives	38

Preferred Solution	38
Implementation Considerations	40
Public & Stakeholder Consultation	41
Local Advisory Committee (LAC)	41
Public Open House # 1	41
Public Open House # 2	42
Public Open House # 3	43
Appendix A	Water Distribution System Analysis
Appendix B	Sanitary Sewer System Analysis
Appendix C	Stormwater Management Supporting Documentation
Appendix D	Public Consultation

Storm Drainage & Stormwater Management (SWM)

The City's Wet Weather Flow Management Guidelines (WWFMG) provide a comprehensive methodology for guiding the design of stormwater management measures for developments and are expected to result in an overall reduction in stormwater volumes and peak flows to levels which are at or below the capacity of the receiving drainage system. For instance, the WWFMG considers the detention of drainage for storms up to the 100-year return period frequency with a stringently controlled discharge rate. It is expected that many of the properties in the study area currently do not deliver this level of performance and, therefore, upon re-development, the adoption of such practices are expected to reduce the hydraulic loading on the receiving drainage systems. In addition to runoff quantity control, the WWFMG contains provisions for water balance – which reduces the amount of runoff exiting the site – and water quality control.

As noted earlier, the recommendations of the Basement Flooding Study Area Class EAs provide significant guidance on system improvements required to minimize the probability and frequency of flooding in the drainage sheds relevant to this study area. As at the time of preparation, the scheduled infrastructure upgrades in the vicinity of the study area resulting from the Basement Flooding Study Area work include improvements on Jane Osler Boulevard in 2014²³. The purpose of this study is not to address current basement flooding issues, but rather to identify improvements needed to service growth in the study area and without exacerbating current conditions.

Given the configuration of the study area and the nature of Dufferin Street and other existing roadways, there is generally little opportunity to implement centralized measures to address stormwater management objectives. On the other hand, the re-development of individual sites will necessitate observance of the WWFMG, thereby resulting in the improved rainfall-runoff characteristics of, and potential reductions in overland flow within, the overall study area relative to current conditions.

Additional information is provided in Appendix C.

STORMWATER MANAGEMENT OBJECTIVES

All existing properties and anticipated development blocks in the study area are expected to be less than 5.0 ha in size, qualifying as “small new developments” pursuant to the WWFMG document. The following are the applicable objectives and requirements for such developments:

Water Balance

Developments are required to retain all runoff from a 5 mm rainfall event through infiltration, evapotranspiration and rainwater reuse. Despite this, it may be worthwhile considering a higher target for developments in this study area given the known historic flooding concerns associated with heavy rainfalls. A review of the available geotechnical information suggests that the underlying soils in the study area, while expected to be capable of modest amounts of infiltration, are not expected to be suitable for more aggressive targets in this regard (see Appendix C). Accordingly, the target 5 mm volume noted above is to be maintained for developments in the study area. Of course, higher captured runoff volumes (rainfall depths) should be welcomed and encouraged, offering the simultaneous benefit of assisting to achieve water quality objectives.




Measures which can be considered to achieve water balance objectives include (but are not necessarily limited to):

-  Green²⁴ or Blue²⁵ Roofs
-  Infiltration Chambers/Galleries

²³ K. Crowther, personal communication, 05 September 2013

²⁴ Relevant Resources: Toronto Green Roof By-Law; Toronto Green Roof Biodiverse Guidelines; Toronto Green Roof Construction Standards; Toronto Green Standard. See www.toronto.ca/greenroofs.

²⁵ Blue roofs are non-vegetated source controls that detain stormwater, preferably with light coloured roofing material.

-  Permeable Pavement
-  Bioretention
-  Rainwater Harvesting

It is important to note that the appropriateness of each of these measures, used alone or in some combination, is dependent upon a variety of factors including development size, actual soil characteristics, capital cost and maintenance considerations as well as intensity of demand for reuse in the case of rainwater harvesting. It is expected that the larger sites will have opportunities to implement several of these measures, while the smaller sites will be quite limited. As with current protocols for development in the City, it will be the development proponent's responsibility to demonstrate that the water balance objective is being achieved.

Water Quality

Developments are required to achieve a long-term average total suspended solids (TSS) removal from runoff of 80% on an annual loading basis, with the overall site removal efficiency including runoff retention and other on-site controls (i.e., treatment train approach). An example of a linkage between measures which provide the dual benefit of water balance and water quality is captured in the following passage:

Bioretention provides effective removal for many pollutants as a result of sedimentation, filtering, soil adsorption, microbial processes and plant uptake. It is also important to note that there is a relationship between the water balance and water quality functions. If a bioretention cell infiltrates and evaporates 100% of the runoff from a site, then there is essentially no pollution leaving the site in surface runoff.²⁶

Similar to the case for water balance, smaller sites are anticipated to be somewhat more challenged at meeting the water quality criterion and limited in the options available to be practically deployed. Historically, oil-grit separators have been used in such situations, however, the performance of most such technologies are deemed by Toronto to achieve at most 50% TSS removal and such devices must be accompanied by other measures in a treatment train to achieve the desired 80% TSS removal target. Media filtration devices with small footprints and capable of controlling finer particles (pollutants), comparable in size to traditional oil-grit separators, are available and which are capable of achieving the water quality target have been deployed on development projects elsewhere in the City, as an alternative. It is noted that operational and cost considerations may favour low impact development (LID) technologies over oil-grit separators.

Flood Flow Management

As noted earlier, the primary cause of historic flooding complaints has been the overwhelming of the capacity of the existing storm and sanitary sewage conveyance systems in response to heavy rainfalls. Although it is not the mandate of this study to resolve the existing causes of flooding as these are being handled under the City's Basement Flooding Protection Program; however, measures to decrease flows from the re-development sites will be required through the WWFMG, and are expected to relieve some of the stress of the receiving drainage system.

Discharge Criteria to Municipal Infrastructure

The allowable release rate to the municipal storm sewer system is governed by the lesser of the peak pre-development runoff rate or the available capacity of the receiving sewer. To estimate the pre-development peak runoff rate, a maximum runoff coefficient of 0.5 may be used, irrespective of the actual pre-development imperviousness of the site.

²⁶ "Low Impact Development Stormwater Management Planning and Design Guide", CVC/TRCA, 2010, Page 4-71.

ALTERNATIVES

The following is a brief description of the Master Plan alternatives considered in the context of storm drainage:

Alternative 1: Do Nothing

This alternative considers no changes to the existing system.

Alternative 2: Expand and/or Upgrade Existing Infrastructure

This alternative considers the implementation of infrastructure to extend the existing storm drainage system such as the case of new roadways to be implemented. The City's current Wet Weather Flow Management Policy requires that flows be controlled to within the limits of the existing system's capacity, subject to additional considerations, and therefore the option of upgrading existing infrastructure (i.e., increasing conveyance) is not applicable in this context.

Alternative 3: Implement On-Site Best Practices

In the context of storm drainage, this alternative considers the implementation of stormwater management measures both on individual development sites as well as within potential roadways. Stormwater management measures would have the effect of reducing and/or controlling runoff volumes exiting the site. They also offer water quality benefits and may also address water balance objectives, depending on site suitability. The City has adopted a Wet Weather Flow Management Guideline (WWFMG) document that has detailed information to guide design practices in this regard.

Alternative 4: Limit Community Growth

This alternative is deemed to not be applicable in this context and is accordingly not considered further for evaluation, but is presented here for the sake of completeness and consistency with the remainder of this document. The rationale underlying this position is based on the fact that this option does not decrease storm runoff. Moreover, the existing hydrology within the study area is characterized by hard surfaces such that any re-development of the lands would not materially exacerbate this condition given that the WWFMG would continue to be applied as per current City policy.

ASSESSMENT & EVALUATION OF ALTERNATIVES

Table 7 Assessment & Evaluation of Alternatives – Storm Drainage & Stormwater Management (SWM)

Criteria	Sub-Criteria	Alternative 1: Do Nothing	Alternative 2: Expand/Upgrade Ex. Infrastructure	Alternative 3: Implement On-Site Best Practices	Alternative 4: Limit Growth
Technical Merit	Functionality	This alternative is not in compliance with the City's existing policies and guidelines.	New storm sewers constructed in new roads have minimal impacts.	No negative environmental impacts.	Not applicable.
	Constructability				
	Maintenance Requirements				
	Life-Cycle Costs				
Natural Environment	Impact on the Natural Environment	This alternative does not consider extension of services into new roads.	Also, construction activities may impact the local environment (e.g., noise, vibration), although these are not expected to be significant in relation to the overall construction activity. Mitigation measures to be implemented.	Reduction in runoff and quality controls will improve environmental health of watershed and reduce hydraulic loading to receiving drainage system.	Existing hydrology of study area is predominantly impervious and any new development will be subject to application of the City's Wet Weather Flow Management Guidelines.
Socio-Economic Environment	Cultural Heritage Impact				
	Construction Impact				
	Residential and Business Impact				
Preferred Solution		Expand existing system into any new roads. Guided application of wet weather flow management guidelines for all new (re-)developments. Encourage the "greening" of all public and private spaces.			

PREFERRED SOLUTION

The preferred solution consists of the following elements:

Expand Existing System into New Roads

Where new public roads are to be developed, the expansion of the existing storm sewer system into these roads for purposes of collecting and conveying drainage from new development sites as well as runoff originating on the roads themselves is a sensible standard practice. Runoff from new sewer systems will need to be limited in accordance with the City's Wet Weather Flow Management Guidelines discharge criteria (e.g., the lesser of: flow rate calculated with a runoff coefficient of 0.5; existing discharge rate; or the *pro rata* share of receiving sewer system capacity).

Guided Application of the City's Wet Weather Flow Management Guidelines (WWFMG)

In general, the City's WWFMG are to be applied for any developments in the study area with one modification relating to the discharge criteria to the local municipal infrastructure where release rates from each site are to be controlled to 75 L/s/ha. It is important to note that this applies only to areas which currently drain to the storm drainage system within the study area, and not to areas that drain to systems outside thereof²⁷.

²⁷ As a specific example, the storm drainage from Yorkdale Shopping Centre is currently directed easterly, away from the study area and, accordingly, any development activity or similar situations which cause changes in the way drainage is handled on this site must consider the context of the system currently accepting such drainage. Of course, this does not preclude the opportunity for specific

It is noted that this release rate (i.e., 75 L/s/ha) is lower than what would be calculated through strict application of the WWFMG in consideration of the known flooding concerns in the area and their direct relationship to stormwater runoff. Additional discussion on the formulation of this criterion is provided in Appendix C.

For greater clarity, the runoff resulting from the 100-year return period design storm is to be contained on site and released at or below the control rate established using the above criteria. This is expected to greatly reduce the amount of water entering the municipal sewers and road surfaces for most rainfalls.

“Greening”

The application of the WWFMG implies the implementation of green measures to control runoff from sites. Nevertheless, additional “greening” of private sites as well as on public roadways wherever practical is generally expected to lead to additional environmental benefits and represents good practice.


Project Schedules

The extension of the storm drainage system into new roadways is a **Schedule A** activity. That is, these projects are approved and may proceed. The other elements of the preferred solution are either private-side controls or general “greening” measures, neither of which require fulfilment of the Class EA process in this context.



Mitigation Measures

Of the few impacts associated with the extension of the storm drainage system into new roadways, they are all relatively minor and straightforward to deal with using standard, customary mitigation practices.

Environmental Impacts

-  **Sedimentation and Dust Control** is required for all construction activities in the City of Toronto. The implementation of standard mitigation practices (e.g., silt fences, mud mats, etc.) are expected to provide adequate controls in this regard, and it is expected that this construction will occur concurrently with other construction activities in the roadway, thereby minimizing the duration during which these impacts may be felt.

Social Impacts

-  **Traffic, Noise and Vibration** result from almost all construction activities of this nature. Similar to the above, standard mitigation practices are expected to provide adequate controls in this regard, and construction is expected to occur concurrently with other construction activities in the roadway, thereby minimizing the duration during which these impacts may be felt.
-  **Safety During Construction** for both workers and the general public is of obvious importance. All construction practices will be required to conform to both the City’s requirements as well as the Province’s legislation in this regard.


studies to be conducted in support of directing storm drainage to other available systems, subject to satisfying the City with respect to the appropriateness thereof.


IMPLEMENTATION CONSIDERATIONS

As with current development planning application processes, the proponent will be responsible for the preparation of Functional Servicing and Stormwater Management Reports in support of any applications. These reports should clearly document how the proposed servicing strategy for the development in question satisfies the WWFMG, as modified by the Preferred Solution noted above.


For larger sites, it may become necessary to test the impact of the development on the receiving downstream sewer network to determine whether there might be adverse impacts on the performance of the sewer system, depending on the extent of implementation of measures identified in the relevant Basement Flooding Study Area Class EAs. The need for this work should be established in consultation with Toronto Water and can be undertaken with the use of the InfoWorks CS dynamic hydraulic models developed as part of the Basement Flooding Study Area Class EAs.

Very small sites may be challenged to meet the guideline relating to water balance or water quality control. In such instances, it should be demonstrated by the development proponent that meeting these guidelines would be either overly burdensome or impossible. As an alternative in these cases, the City may consider accepting cash-in-lieu financial contributions which may be applied toward other improvements in the same watershed. Similarly, smaller sites may be challenged to meet the 75 L/s/ha controlled release rate criterion and, in such instances, the City may consider accepting vortex-flow control devices that offer lower release rates with protection against clogging.





CONTRACTOR TO BE ADVISED THAT THE CONDITION OF THE EXISTING PLAN IS SUBJECT TO THE CITY OF TORONTO'S RECORD DRAWINGS AND AS A RESULT OF DEMOLITION AND REMOVAL OF EXISTING STRUCTURES.



LEGEND

- DENOTES SANITARY MANHOLE
- DENOTES STORM MANHOLE
- DENOTES CATCHBASIN/DOUBLE CATCHBASIN WITH GROSS TRAPS
- DENOTES AREA DRAIN
- DENOTES INVERT AND BOX
- DENOTES WATER METER AND BACKFLOW PREVENTER
- DENOTES PROPERTY LINE
- DENOTES OVERLAND FLOW ARROW
- DENOTES PROPOSED ELEVATION
- DENOTES PROPOSED BOTTOM OF CURB
- DENOTES PROPOSED TOP OF RETAINING WALL
- DENOTES EXISTING ELEVATION
- DENOTES SURFACE PONDING
- DENOTES SITE PLAN APPLICATION No. 21 10823 INV. OR SA (REFER TO SCHAFFERS PROJECT No. 466 SITE PLAN)

NOTE:

1. FOR SECTIONS 1 TO 3 REFER TO DMS. SEC-1

PRIOR TO COMMENCING ANY WORK WITHIN THE MUNICIPAL RIGHT-OF-WAY, THE CONTRACTOR SHALL OBTAIN ALL NECESSARY ROAD OCCUPANCY PERMITS FROM THE CITY'S RIGHT-OF-WAY MANAGEMENT SECTION. CONTACT 416-394-8422.

TORONTO BENCH MARK No. NY18017
 ELEVATIONS SHOWN HEREON ARE GEODETIC AND ARE REFERRED TO THE ELEVATION OF MEAN SEA LEVEL. NY18017 HAVING A PUBLISHED ELEVATION OF 103.558 METERS.

DIGITAL INFORMATION

No.	DATE	REVISIONS	T.A.	INITIAL SIGNED
1.	JUL 20 2021	FIRST ENGINEERING SUBMISSION TO CITY		

SCHAFFERS
 CONSULTING ENGINEERS
 6 Bloor Street East, Toronto, ON M4W 1A5
 Phone: (416) 593-1100
 Fax: (416) 593-6675
 Email: info@schaffers.com

ENGINEERING & CONSTRUCTION SERVICES DIVISION
 ACCEPTED TO BE IN ACCORDANCE WITH THE CITY OF TORONTO STANDARDS THE ACCEPTED PRACTICE IN THE PROFESSION OF ENGINEERING CONTENT.

3450 DUFFERIN STREET
 CITY OF TORONTO
 GRADING PLAN

DESIGN	T.A.	DRAWN	M.P.	CHECKED	H.S.	PROJECT No.
SCALE	1:400					2020-49166
DATE	JUNE 2016					GR-1

3400 DUFFERIN STREET

APPLICATION FOR ZONING BY-LAW AMENDMENT

PROJECT TEAM

DEVELOPER
Collector
20 Eglington Ave W, Suite 1700
Toronto, ON, M8G 1K8
T: 416-945-8000
collectordev.com

ARCHITECTURAL & LANDSCAPE ARCHITECTURE
gh3
T: 416-915-1791
gh3.ca

PLANNING & URBAN DESIGN
Boufflerie
T: 416-947-8744
boufflerie.ca

CIVIL ENGINEERING
BP GROUP
T: 905-763-2822
bpgroup.com

WIND & ARBORIST
S&S Consulting
T: 226-756-8888
sncsconsulting.com

TRANSPORTATION
BP GROUP
T: 416-961-7110
bpgroup.com

STRUCTURAL
TSD

MECHANICAL & ELECTRICAL
TSD

ARCHITECTURAL SHEET LIST

Sheet	Drawing Name	Current Revision
A000 PROJECT INFORMATION		
A000	COVER SHEET	
A001	STATISTICS	
A100 SITE		
A100	CONTEXT PLAN	
A101	SURVEY	
A102	ROOF PLAN	
A103	GROUND FLOOR SITE PLAN	
A105	LEVEL P1 FLOOR PLAN	
A200 PLANS		
A200	LEVEL 1 FLOOR PLAN	
A201	LEVEL 2 FLOOR PLAN	
A202	LEVEL 3 FLOOR PLAN	
A203	LEVEL 4 FLOOR PLAN	
A204	LEVEL 5 FLOOR PLAN	
A205	LEVEL 6 FLOOR PLAN	
A206	LEVEL 7 FLOOR PLAN	
A208	LEVEL 8 FLOOR PLAN	
A209	LEVEL 10 FLOOR PLAN	
A210	LEVEL 11-20 FLOOR PLAN	
A300 ELEVATIONS		
A300	SITE ELEVATIONS	
A301	SITE ELEVATIONS	
A302	BUILDING A ELEVATIONS	
A303	BUILDING B ELEVATIONS	
A304	BUILDING C ELEVATIONS	
A400 SECTIONS		
A400	SITE SECTIONS	
A401	SITE SECTIONS	
A402	SITE SECTIONS	
A500 MASSING VIEW		
A500	MASSING VIEW	
L100 PLANS		
L101	LANDSCAPE PLAN	1
L102	LANDSCAPE ROOF PLANS	
L103	PLANTING & SOIL VOLUME PLAN	1
L400 DETAILS		
L401	LANDSCAPE DETAILS	
L402	LANDSCAPE DETAILS	
L403	COY TYP DETAILS	

Rev. Date Issued



gh3
gh3*
55 DUNDAS ST. W. SUITE 100
TORONTO, ON, CANADA M5G 1P9
416 915 1791

COLLECTOR
3400 DUFFERIN STREET



SCALE
PROJECT NO. 202211
ISSUE DATE -

COVER SHEET

A000

1.0 SUMMARY

GRAND SITE AREA: 16,860 m²
 TOTAL GFA: 20,811 m²
 FSR: 1.35
 NEW RESIDENTIAL UNITS: 514

PART B - BUILDING A
 SITE AREA: 4,082 m²
 GFA: 27,241 m²
 FSR: 6.9
 NEW RESIDENTIAL UNITS: 303

PART B - BUILDING B
 SITE AREA: 4,072 m²
 GFA: 26,571 m²
 FSR: 6.9
 NEW RESIDENTIAL UNITS: 311

PART E - BUILDING C
 SITE AREA: 1,811 m²
 GFA: 3,805 m²
 FSR: 2.1
 NEW RESIDENTIAL UNITS: 75

3.0 FLOOR AREA

*GFA calculated per Area Plans A1001 - A1003

Level		2.2 FLOOR AREA		GFA		Amenity											
		# of Levels	GCA/Level (m ²)	Total GCA (m ²)	GCA (m ²)	Residential GCA (m ²)	Residential GCA (m ²)	Loading GCA (m ²)	Parking GCA (m ²)	GFA Deductions (m ²)	GFA (SF)	GFA (m ²)	Residential GFA (m ²)	(Non-Res/ Retail GFA (m ²))	Leasable (m ²)	Indoor Amenity (m ²)	Outdoor Amenity (m ²)
BELOW GRADE																	
P2	1	859 m ²	859 m ²	859 m ²	859 m ²	859 m ²	0 m ²	859 m ²	859 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²
P1	1	818 m ²	818 m ²	818 m ²	818 m ²	818 m ²	0 m ²	818 m ²	818 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²
BELOW GRADE TOTAL		1	1776 m ²	1676 m ²	1676 m ²	1676 m ²	0 m ²	1676 m ²	1676 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²


BUILDING A																	
Level	# of Levels	GCA/Level (m ²)	Total GCA (m ²)	GCA (m ²)	Residential GCA (m ²)	Residential GCA (m ²)	Loading GCA (m ²)	Parking GCA (m ²)	GFA Deductions (m ²)	GFA (SF)	GFA (m ²)	Residential GFA (m ²)	(Non-Res/ Retail GFA (m ²))	Leasable (m ²)	Indoor Amenity (m ²)	Outdoor Amenity (m ²)	
Level 1	1	2530 m ²	2530 m ²	2530 m ²	2530 m ²	2530 m ²	345 m ²	0 m ²	717 m ²	1813 m ²	1722 m ²	1722 m ²	0 m ²	1084 m ²	89 m ²	0 m ²	
Level 2	1	2478 m ²	2478 m ²	2478 m ²	2478 m ²	2478 m ²	0 m ²	0 m ²	95 m ²	2383 m ²	2292 m ²	2292 m ²	0 m ²	1678 m ²	0 m ²	0 m ²	
Level 3	1	2478 m ²	2478 m ²	2478 m ²	2478 m ²	2478 m ²	0 m ²	0 m ²	291 m ²	2187 m ²	1928 m ²	1928 m ²	0 m ²	1678 m ²	0 m ²	0 m ²	
Level 4	1	2478 m ²	2478 m ²	2478 m ²	2478 m ²	2478 m ²	0 m ²	0 m ²	95 m ²	2383 m ²	2292 m ²	2292 m ²	0 m ²	1678 m ²	0 m ²	0 m ²	
Level 5	1	2274 m ²	2274 m ²	2274 m ²	2274 m ²	2274 m ²	0 m ²	0 m ²	80 m ²	2194 m ²	1914 m ²	1914 m ²	0 m ²	1762 m ²	0 m ²	0 m ²	
Level 6	1	2388 m ²	2388 m ²	2388 m ²	2388 m ²	2388 m ²	0 m ²	0 m ²	126 m ²	2262 m ²	1916 m ²	1916 m ²	0 m ²	1762 m ²	0 m ²	0 m ²	
Level 7	1	1214 m ²	1214 m ²	1214 m ²	1214 m ²	1214 m ²	0 m ²	0 m ²	312 m ²	1012 m ²	942 m ²	942 m ²	0 m ²	657 m ²	277 m ²	0 m ²	
Level 8	1	1034 m ²	1034 m ²	1034 m ²	1034 m ²	1034 m ²	0 m ²	0 m ²	296 m ²	738 m ²	689 m ²	689 m ²	0 m ²	601 m ²	227 m ²	224 m ²	
Level 9	1	794 m ²	794 m ²	794 m ²	794 m ²	794 m ²	0 m ²	0 m ²	58 m ²	736 m ²	698 m ²	698 m ²	0 m ²	701 m ²	0 m ²	0 m ²	
Level 10	1	794 m ²	794 m ²	794 m ²	794 m ²	794 m ²	0 m ²	0 m ²	93 m ²	701 m ²	604 m ²	604 m ²	0 m ²	701 m ²	0 m ²	0 m ²	
Level 11-29	19	794 m ²	14983 m ²	14983 m ²	14983 m ²	14983 m ²	0 m ²	0 m ²	953 m ²	14030 m ²	13200 m ²	13200 m ²	0 m ²	13200 m ²	0 m ²	0 m ²	
BUILDING A TOTAL		1	30995 m ²	33027 m ²	30995 m ²	33027 m ²	345 m ²	0 m ²	3046 m ²	30081 m ²	27947 m ²	27947 m ²	0 m ²	24695 m ²	599 m ²	224 m ²	

BUILDING B																	
Level	# of Levels	GCA/Level (m ²)	Total GCA (m ²)	GCA (m ²)	Residential GCA (m ²)	Residential GCA (m ²)	Loading GCA (m ²)	Parking GCA (m ²)	GFA Deductions (m ²)	GFA (SF)	GFA (m ²)	Residential GFA (m ²)	(Non-Res/ Retail GFA (m ²))	Leasable (m ²)	Indoor Amenity (m ²)	Outdoor Amenity (m ²)	
Level 1	1	2342 m ²	2342 m ²	2342 m ²	1131 m ²	1211 m ²	359 m ²	0 m ²	672 m ²	1670 m ²	1579 m ²	1579 m ²	0 m ²	1077 m ²	1396 m ²	134 m ²	
Level 2	1	1855 m ²	1855 m ²	1855 m ²	1855 m ²	1855 m ²	0 m ²	0 m ²	98 m ²	1757 m ²	1659 m ²	1659 m ²	0 m ²	1427 m ²	0 m ²	0 m ²	
Level 3	1	2218 m ²	2218 m ²	2218 m ²	1937 m ²	2129 m ²	0 m ²	0 m ²	94 m ²	2124 m ²	1929 m ²	1929 m ²	0 m ²	2063 m ²	0 m ²	0 m ²	
Level 4	1	2218 m ²	2218 m ²	2218 m ²	2126 m ²	2282 m ²	0 m ²	0 m ²	94 m ²	2124 m ²	2032 m ²	2032 m ²	0 m ²	2063 m ²	0 m ²	0 m ²	
Level 5	1	2155 m ²	1977 m ²	2128 m ²	1977 m ²	2128 m ²	0 m ²	0 m ²	94 m ²	2033 m ²	1883 m ²	1883 m ²	0 m ²	1873 m ²	0 m ²	0 m ²	
Level 6	1	2155 m ²	1977 m ²	2128 m ²	1977 m ²	2128 m ²	0 m ²	0 m ²	94 m ²	2033 m ²	1883 m ²	1883 m ²	0 m ²	1873 m ²	0 m ²	0 m ²	
Level 7	1	1322 m ²	1322 m ²	1322 m ²	977 m ²	1059 m ²	0 m ²	0 m ²	327 m ²	995 m ²	965 m ²	965 m ²	0 m ²	657 m ²	297 m ²	540 m ²	
Level 8	1	1034 m ²	1034 m ²	1034 m ²	739 m ²	817 m ²	0 m ²	0 m ²	355 m ²	679 m ²	631 m ²	631 m ²	0 m ²	648 m ²	227 m ²	231 m ²	
Level 9	1	794 m ²	794 m ²	794 m ²	747 m ²	809 m ²	0 m ²	0 m ²	49 m ²	745 m ²	697 m ²	697 m ²	0 m ²	702 m ²	0 m ²	0 m ²	
Level 10	1	794 m ²	794 m ²	794 m ²	746 m ²	809 m ²	0 m ²	0 m ²	49 m ²	745 m ²	697 m ²	697 m ²	0 m ²	702 m ²	0 m ²	0 m ²	
Level 11-29	19	794 m ²	14983 m ²	14983 m ²	14184 m ²	15287 m ²	0 m ²	0 m ²	609 m ²	14281 m ²	13245 m ²	13245 m ²	0 m ²	13333 m ²	0 m ²	0 m ²	
BUILDING B TOTAL		1	29873 m ²	32100 m ²	29153 m ²	30380 m ²	359 m ²	0 m ²	2907 m ²	29031 m ²	26294 m ²	26294 m ²	0 m ²	19737 m ²	647 m ²	770 m ²	

BUILDING C																	
Level	# of Levels	GCA/Level (m ²)	Total GCA (m ²)	GCA (m ²)	Residential GCA (m ²)	Residential GCA (m ²)	Loading GCA (m ²)	Parking GCA (m ²)	GFA Deductions (m ²)	GFA (SF)	GFA (m ²)	Residential GFA (m ²)	(Non-Res/ Retail GFA (m ²))	Leasable (m ²)	Indoor Amenity (m ²)	Outdoor Amenity (m ²)	
Level 1	1	1035 m ²	1035 m ²	1116 m ²	244 m ²	2624 m ²	446 m ²	0 m ²	610 m ²	4578 m ²	425 m ²	137 m ²	298 m ²	266 m ²	0 m ²	504 m ²	
Level 2	1	973 m ²	973 m ²	1077 m ²	973 m ²	1047 m ²	0 m ²	0 m ²	42 m ²	1003 m ²	931 m ²	931 m ²	0 m ²	786 m ²	59 m ²	0 m ²	
Level 3	1	973 m ²	973 m ²	1077 m ²	973 m ²	1047 m ²	0 m ²	0 m ²	42 m ²	1003 m ²	931 m ²	931 m ²	0 m ²	786 m ²	59 m ²	0 m ²	
Level 4	1	626 m ²	626 m ²	8934 m ²	759 m ²	8168 m ²	0 m ²	0 m ²	110 m ²	7714 m ²	717 m ²	717 m ²	0 m ²	668 m ²	67 m ²	0 m ²	
Level 5	1	626 m ²	626 m ²	8934 m ²	759 m ²	8168 m ²	0 m ²	0 m ²	110 m ²	7714 m ²	717 m ²	717 m ²	0 m ²	668 m ²	67 m ²	0 m ²	
Level 6	1	626 m ²	626 m ²	8934 m ²	759 m ²	8168 m ²	0 m ²	0 m ²	110 m ²	7714 m ²	717 m ²	717 m ²	0 m ²	668 m ²	67 m ²	0 m ²	
Level 7	1	518 m ²	473 m ²	5089 m ²	473 m ²	5089 m ²	0 m ²	0 m ²	167 m ²	3659 m ²	3365 m ²	3365 m ²	0 m ²	416 m ²	135 m ²	0 m ²	
Level 8	1	473 m ²	473 m ²	5089 m ²	473 m ²	5089 m ²	0 m ²	0 m ²	42 m ²	4637 m ²	431 m ²	431 m ²	0 m ²	366 m ²	0 m ²	0 m ²	
Level 9	1	473 m ²	473 m ²	5089 m ²	473 m ²	5089 m ²	0 m ²	0 m ²	42 m ²	4637 m ²	431 m ²	431 m ²	0 m ²	366 m ²	0 m ²	0 m ²	
Level 10	1	170 m ²	170 m ²	1828 m ²	0 m ²	170 m ²	0 m ²	0 m ²	170 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	0 m ²	
BUILDING C TOTAL		1	7040 m ²	79871 m ²	5760 m ²	61983 m ²	446 m ²	0 m ²	1444 m ²	60329 m ²	5605 m ²	5371 m ²	298 m ²	5081 m ²	446 m ²	504 m ²	
GRAND TOTAL		1	63301 m ²	69917 m ²	61962 m ²	68386 m ²	1149 m ²	0 m ²	24296 m ²	64269 m ²	59811 m ²	59441 m ²	138 m ²	34693 m ²	1646 m ²	1481 m ²	

4.0 AMENITY

Total Units		4.1 AMENITY			



NOTE: FOOTPRINT INCLUSION OF BUILDING AREA IS IN MEASURING PROPERTIES

SHARED PRIVATE DRIVE

DUFFERIN STREET

NEW MUNICIPAL ROAD

JANE OSLER BOULEVARD

GREEN ROOF STATISTICS - BUILDING A

Available Roof Space Calculation	Required	Provided
Gross Roof Area, as defined in Green Roof By-law(s)	-	7
Total Roof Area	2413	2413
Area of Residential Private Terrace (m ²)	-	-
Roofing Material Storage Space, as a Residential Building (m ²)	187 - 122 = 65	-
Area of Residential Energy Storage (m ²)	-	-
Area of Mechanical Plant Room (m ²)	-	-
Area of Other Area with Roof pitch less than 7.5% (m ²)	-	-
Total Available Roof Space (m ²)	-	1986
Green Roof Coverage	-	82%
Coverage of Available Roof Space (m ²)	198	198
Coverage of Available Roof Space (%)	8%	8%

GREEN ROOF STATISTICS - BUILDING B

Available Roof Space Calculation	Required	Provided
Gross Roof Area, as defined in Green Roof By-law(s)	-	920
Total Roof Area	920	920
Area of Residential Private Terrace (m ²)	-	-
Roofing Material Storage Space, as a Residential Building (m ²)	341 - 248 = 93	-
Area of Residential Energy Storage (m ²)	-	-
Area of Mechanical Plant Room (m ²)	-	-
Area of Other Area with Roof pitch less than 7.5% (m ²)	-	-
Total Available Roof Space (m ²)	-	1689
Green Roof Coverage	-	18%
Coverage of Available Roof Space (m ²)	303	1029
Coverage of Available Roof Space (%)	18%	10%

GREEN ROOF STATISTICS - BUILDING C

Available Roof Space Calculation	Required	Provided
Gross Roof Area, as defined in Green Roof By-law(s)	-	154
Total Roof Area	154	154
Area of Residential Private Terrace (m ²)	-	-
Roofing Material Storage Space, as a Residential Building (m ²)	341 - 248 = 93	-
Area of Residential Energy Storage (m ²)	-	-
Area of Mechanical Plant Room (m ²)	-	-
Area of Other Area with Roof pitch less than 7.5% (m ²)	-	-
Total Available Roof Space (m ²)	-	211
Green Roof Coverage	-	14%
Coverage of Available Roof Space (m ²)	291	302
Coverage of Available Roof Space (%)	38%	33%

Rev. Date Issued



gh3
957
55 OSSINGTON AVE. SUITE 100
TORONTO, ON CANADA M5V 2Y9
416 915 1791


COLLECTIVE
3400 DUFFERIN STREET



SCALE As indicated
PROJECT NO. 202211
ISSUE DATE -

ROOF PLAN

A102



S1 CAR PARKING						
Level	Residential Car Parking			Visitor Car Parking		
	Regular	BP	Total	Regular	BP	Total
P1	0	0	0	0	2	2
	0	0	0	0	2	2
BUILDING A						
P1	36	3	39	32	1	33
P2	88	13	101	0	0	0
	125	16	141	32	1	33
BUILDING B						
P1	60	0	60	0	0	0
P2	85	0	85	0	0	0
	145	0	145	0	0	0
BUILDING C						
P1	15	0	15	0	0	0
P2	24	0	24	0	0	0
	39	0	39	0	0	0
TOTAL	300	19	319	32	1	33



gh3
 985*
 55 OSSINGTON AVE. SUITE 100
 TORONTO, ON CANADA M6J 2Y9
 416 915 1791

COLLECTIVE
 3400 SHEPPARD STREET



TORONTO
 SCALE 1:200
 PROJECT NO. 202211
 ISSUE DATE

**LEVEL P1
 FLOOR PLAN**

URBAN X - SUBSURFACE UTILITY ENGINEERING

GENERAL NOTES:

- 1. THE INFORMATION SHOWN ON THIS PLAN IS BASED ON THE DATA PROVIDED BY THE CLIENT AND THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED.
- 2. THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED AND HAS FOUND THAT THE DATA PROVIDED IS SUFFICIENT FOR THE PURPOSES OF THIS PLAN.
- 3. THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED AND HAS FOUND THAT THE DATA PROVIDED IS SUFFICIENT FOR THE PURPOSES OF THIS PLAN.
- 4. THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED AND HAS FOUND THAT THE DATA PROVIDED IS SUFFICIENT FOR THE PURPOSES OF THIS PLAN.
- 5. THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED AND HAS FOUND THAT THE DATA PROVIDED IS SUFFICIENT FOR THE PURPOSES OF THIS PLAN.
- 6. THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED AND HAS FOUND THAT THE DATA PROVIDED IS SUFFICIENT FOR THE PURPOSES OF THIS PLAN.
- 7. THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED AND HAS FOUND THAT THE DATA PROVIDED IS SUFFICIENT FOR THE PURPOSES OF THIS PLAN.
- 8. THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED AND HAS FOUND THAT THE DATA PROVIDED IS SUFFICIENT FOR THE PURPOSES OF THIS PLAN.
- 9. THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED AND HAS FOUND THAT THE DATA PROVIDED IS SUFFICIENT FOR THE PURPOSES OF THIS PLAN.
- 10. THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED AND HAS FOUND THAT THE DATA PROVIDED IS SUFFICIENT FOR THE PURPOSES OF THIS PLAN.

SEE GROUND LEVEL DESCRIPTION AND UTILITY EXISTENCE

THE INFORMATION SHOWN ON THIS PLAN IS BASED ON THE DATA PROVIDED BY THE CLIENT AND THE ENGINEER HAS CONDUCTED VISUAL GENERAL VERIFICATION OF THE DATA PROVIDED.

UNDERGROUND UTILITY CODES AND COLOUR

LEGEND:

CL	CLAY	CYAN
CO	CONCRETE	RED
CU	CUPRO	PURPLE
CS	CORROSION RESISTANT STEEL	GREEN
ST	STEEL	ORANGE
SA	STEEL PIPE	BROWN
VI	VERTICAL IRON	BLACK
LA	LOW VOLTAGE	BLUE
VS	VENT	PINK
AV	AIR	PURPLE
HA	HIGH VOLTAGE	RED
TE	TELEPHONE	PURPLE
SI	STEEL	PURPLE
SE	SEWER	BROWN
ST	STEEL	ORANGE
SA	STEEL PIPE	BROWN

ORIGIN: UNIVERSITY OF TORONTO, 2010

SYMBOLS: [Various symbols for utility types]

SUBSURFACE UTILITY ENGINEERING STUDY

at

3400 DUFFERIN STREET TORONTO, ONTARIO


FOR: IBI PROFESSIONAL SERVICES

DATE: JULY 26, 2022
CHECKED BY: RB/ET

PROJECT #: 139570
SCALE: 1:250



REVISONS		
DATE	REVISION	INITIALS
2022/07/26	FOR CLIENT REVIEW	J.S.
2022/07/26	FOR PLS 1 - JANEK	J.S.





Form Information

Form Name:	06. V2 Urban-X QL-A Form
Submitter Name:	Mike (4167952891)
Submission Date:	Jul 28, 2022 11:04:52 AM EDT

Project Information

Project Name:	3400 Dufferin
Project Number:	139570
Project Team:	Mike Heifetz

Test Pit Information

Test Pit No.:	1
Excavation Date:	Jul 28, 2022
Excavation Location:	3400 Dufferin St.

Location Map -Choose Satellite Image



Exposed Utility Information

Target Utility:	FOC
Assumed Owner:	Rogers
Target SUE Quality Level:	QL-B
Measured Depth to Utility Top (m)	0.78
Estimated Pipe Diameter (mm)	100
Inferred Material from Surface Observation	Plastic
Exposed Utility Count	1
Additional Utilities Found ?	Yes
Exposed Utility:	FOC
Assumed Owner:	Rogers
Target SUE Quality Level:	QL-B
Measured Depth to Utility Top (m)	0.88
Estimated Pipe Diameter (mm)	60
Inferred Material from Surface Observation	Plastic
Exposed Utility Count	1

Excavation Information

Surface Type:	Natural Ground
Final Hole Depth (m):	1.15
Final Hole Width (m):	0.4
Final Hole Length (m):	0.8
Notes:	Bigger hole due to locate being slightly off.

Test Pit Photos:

Overview of TP Location



Detail of TP Location



Downhole Looking North



Downhole Looking East



Team Members:

Measured By:

Mike Heifetz

GPS By:

Mike Heifetz



Form Information

Form Name:	06. V2 Urban-X QL-A Form
Submitter Name:	Mike (4167952891)
Submission Date:	Jul 28, 2022 11:05:10 AM EDT


Project Information

Project Name:	3400 Dufferin
Project Number:	139570
Project Team:	Mike Heifetz

Test Pit Information

Test Pit No.:	2
Excavation Date:	Jul 28, 2022
Excavation Location:	3400 Dufferin St.

Location Map -Choose Satellite Image



Exposed Utility Information

Target Utility:	EL
Assumed Owner:	Private
Target SUE Quality Level:	QL-B
Measured Depth to Utility Top (m)	0.40
Estimated Pipe Diameter (mm)	20
Inferred Material from Surface Observation	Direct Buried Insulated Cable
Square	No
Exposed Utility Count	1
Additional Utilities Found ?	No

Excavation Information

Surface Type:	Natural Ground
Final Hole Depth (m):	0.5
Final Hole Width (m):	0.3
Final Hole Length (m):	0.3

Test Pit Photos:

Overview of TP Location



Detail of TP Location



Downhole Looking North



Downhole Looking East



Team Members:

Measured By:

Mike Heifetz

GPS By:

Mike Heifetz



Form Information

Form Name:	06. V2 Urban-X QL-A Form
Submitter Name:	Mike (4167952891)
Submission Date:	Jul 28, 2022 11:05:41 AM EDT


Project Information

Project Name:	3400 Dufferin
Project Number:	139570
Project Team:	Mike Heifetz

Test Pit Information

Test Pit No.:	3
Excavation Date:	Jul 28, 2022
Excavation Location:	3400 Dufferin St.

Location Map -Choose Satellite Image



Exposed Utility Information

Target Utility:	SL
Assumed Owner:	Private
Target SUE Quality Level:	QL-B
Measured Depth to Utility Top (m)	0.66
Estimated Pipe Diameter (mm)	40
Inferred Material from Surface Observation	Plastic
Square	No
Exposed Utility Count	1
Additional Utilities Found ?	No

Excavation Information


Surface Type:	Asphalt
Pavement Thickness (mm):	80
Final Hole Depth (m):	0.8
Final Hole Width (m):	0.35
Final Hole Length (m):	0.35

Test Pit Photos:

Overview of TP Location



Detail of TP Location



Downhole Looking North



Downhole Looking East



Team Members:

Measured By:

Mike Heifetz

GPS By:

Mike Heifetz

Appendix B

Stormwater Analysis

Stormwater Design Calculations

Stormfilter Sizing (Contech)

3400 Dufferin Street

Mixed-Use Development

**Overall Development Runoff Coefficients**

Project Name: 3400 Dufferin Street

Project Number: 139570

Date: 28 July 2022

Designed By: Jason Jenkins, P.Eng.

Block B (Building A)				
Conventional Roof	1,387	34.3%	0.90	0.31
Intensive Green Roof	1,088	26.9%	0.50	0.13
Landscape	0	0.0%	0.25	0.00
Landscape over P1	225	5.6%	0.45	0.03
Permeable Pavers	0	0.0%	0.55	0.00
Impervious	1,346	33.3%	0.90	0.30
Total Area	4,046	100%		0.77

Block D (Building B)				
Conventional Roof	1,399	35.0%	0.90	0.31
Intensive Green Roof	1,026	25.6%	0.50	0.13
Landscape	0	0.0%	0.25	0.00
Landscape over P1	571	14.3%	0.45	0.06
Permeable Pavers	0	0.0%	0.55	0.00
Impervious	1,006	25.1%	0.90	0.23
Total Area	4,002	100%		0.73

Block E (Building C)				
Conventional Roof	672	40.7%	0.90	0.37
Intensive Green Roof	362	21.9%	0.50	0.11
Landscape		0.0%	0.25	0.00
Landscape over P1	183	11.1%	0.45	0.05
Permeable Pavers		0.0%	0.55	0.00
Impervious	435	26.3%	0.90	0.24
Total Area	1,652	100.0%		0.76

External Area				
Conventional Roof		0.0%	0.90	0.00
Green Roof		0.0%	0.50	0.00
Landscape	1,471	100.0%	0.25	0.25
Landscape over P1		0.0%	0.45	0.00
Permeable Pavers		0.0%	0.55	0.00
Impervious		0.0%	0.90	0.00
Total Area	1,471	100%		0.25

Municipal ROW				
Conventional Roof	0	0.0%	0.90	0.00
Green Roof	0	0.0%	0.50	0.00
Landscape	1,771	26.7%	0.25	0.07
Landscape over P1	0	0.0%	0.45	0.00
Permeable Pavers	0	0.0%	0.55	0.00
Impervious	4,870	73.3%	0.90	0.66
Total Area	6,641	100%		0.73

Municipal ROW + External Area				
Conventional Roof	0	0.0%	0.90	0.00
Green Roof	0	0.0%	0.50	0.00
Landscape	3,242	40.0%	0.25	0.10
Landscape over P1	0	0.0%	0.45	0.00
Permeable Pavers	0	0.0%	0.55	0.00
Impervious	4,870	60.0%	0.90	0.54
Total Area	8,112	100%		0.64

Overall Subdivision (Not Including External Area)				
Conventional Roof	3,458	21.2%	0.90	0.19
Intensive Green Roof	2,476	15.2%	0.50	0.08
Landscape	1,771	10.8%	0.25	0.03
Landscape over P1	979	6.0%	0.45	0.03
Permeable Pavers	0	0.0%	0.55	0.00
Impervious	7,657	46.9%	0.90	0.42
Total Area:	16,341	100%		0.74

3400 Dufferin Street

Rational Method - 100 Year Storm


Mixed-Use Development

Plan of Subdivision



$$I_{100\text{-year}} = \frac{59.7}{(10)^{0.80}} = 250.32 \text{ mm/hr}$$

Project Name:	3400 Dufferin Street	Area of Municipal ROW + External Drainage Area =		0.8112	
Project Number:	139570	Weighed Runoff Coefficient =		0.64	
Date:	28 July 2022	Orifice Discharge (L/s) =		120.1	
Time (min)	Intensity (mm/hr)	Q-100 (L/s)	Q-Blocks (L/s)	Q-stored (L/s)	Storage Vol. (m ³)
0	0.0	0.000		0.000	0.000
10	250.3	361.121	72.750	313.773	188.264
20	143.8	207.410		160.062	192.074
30	103.9	149.953		102.606	184.690
40	82.6	119.126		71.778	172.267
50	69.1	99.650		52.302	156.907
60	59.7	86.126		38.778	139.600
70	52.8	76.133		28.786	120.899
80	47.4	68.420		21.072	101.145
90	43.2	62.267		14.919	80.565
100	39.7	57.234		9.886	59.317
110	36.8	53.032		5.684	37.517
120	34.3	49.466		2.118	15.253
130	32.2	46.398		0.000	0.000
140	30.3	43.727		0.000	0.000
150	28.7	41.379		0.000	0.000
160	27.2	39.297		0.000	0.000
170	25.9	37.436		0.000	0.000
180	24.8	35.763		0.000	0.000
190	23.7	34.249		0.000	0.000
200	22.8	32.872		0.000	0.000
210	21.9	31.614		0.000	0.000
220	21.1	30.459		0.000	0.000
230	20.4	29.395		0.000	0.000
240	19.7	28.411		0.000	0.000
250	19.1	27.498		0.000	0.000
260	18.5	26.649		0.000	0.000
270	17.9	25.856		0.000	0.000
280	17.4	25.115		0.000	0.000
290	16.9	24.419		0.000	0.000
300	16.5	23.766		0.000	0.000
310	16.0	23.151		0.000	0.000
320	15.6	22.570		0.000	0.000
330	15.3	22.021		0.000	0.000
340	14.9	21.502		0.000	0.000
350	14.6	21.009		0.000	0.000
360	14.2	20.540		0.000	0.000



Storage Volume Required (cu.m) = **192.1**
 Storage Volume Provided (cu.m) = **197.9**
 HGL Depth (m) = 1.2
 Orifice Diameter (mm) = 200

3400 Dufferin Street

Mixed-Use Development



Water Quality Calculations

Plan of Subdivision

Project Name: 3400 Dufferin Street

Project Number: 139570

Date: 28 July 2022

Designed By: Jason Jenkins, P.Eng.

TSS Removal (Un-Treated)

Surface	Area (m ²)		Effective TSS Removal	Overall TSS Removal
Conventional Roof	0	0.0%	80	0.0
Green Roof	0	0.0%	80	0.0
Landscape	1,771	26.7%	80	21.3
Landscape over P1	0	0.0%	80	0.0
Permeable Pavers	0	0.0%	80	0.0
Impervious	4,870	73.3%	0	0.0
Total Area:	6,641	100%		21.3

Treatment Required

TSS Removal (With Treatment)

Surface	Area (m ²)		Effective TSS Removal	Overall TSS Removal
Conventional Roof	0	0.0%	80	0.0
Green Roof	0	0.0%	80	0.0
Landscape	1,771	26.7%	80	21.3
Landscape over P1	0	0.0%	80	0.0
Permeable Pavers	0	0.0%	80	0.0
Impervious	4,870	73.3%	80	58.7
Total Area:	6,641	100%		80.0

Site Meets 80% TSS Removal

3400 Dufferin Street

Mixed-Use Development

**Water Balance Calculations**

Plan of Subdivision

Project Name: 3400 Dufferin Street

Project Number: 139570

Date: 28 July 2022

Designed By: Jason Jenkins, P.Eng.

Total Volume to be Retained	
Required Water Balance (mm):	5.0
Recall ROW Area (m ²):	6,641
Total Water Balance to be Retained (m ³):	33.2

Volume Achieved Through Initial Abstraction				
Surface	Area (m ²)		I.A.	Vol. (m ³)
Conventional Roof	0		1	0.0
Green Roof	0		7	0.0
Landscape	1,771		5	8.9
Landscape over P1	0		5	0.0
Permeable Pavers	0		5	0.0
Impervious	4,870		1	4.9
Total Area:	6,641			13.7

Note: New Municipal Roadway does not meet Water Balance Target

Water Balance Summary for Municipal Roadway		Vol. (m ³)
Total Water Balance to be Retained:		33.2
Total Water Balance Achieved through Initial Abstraction:		13.7
Shortfall to be made up by Development Blocks:		19.5

Water Balance Targets for Development Blocks				Vol. (m ³)
Block B (Building A)	4,046	41.7%	5	20.2
Block D (Building B)	4,002	41.3%	5	20.0
Block E (Building C)	1,652	17.0%	5	8.3
Total Area:	9,700	100%		48.5

Volumetric Adjustments for Development Blocks				Vol. (m ³)
Block B (Building A)	4,046	41.7%		8.1
Block D (Building B)	4,002	41.3%		8.0
Block E (Building C)	1,652	17.0%		3.3
Total Area:	9,700	100%		19.48

Adjusted Water Balance Targets for Development Blocks				Vol. (m ³)
Block B (Building A)	4,046		7.0	28.4
Block D (Building B)	4,002		7.0	28.0
Block E (Building C)	1,652		7.0	11.6
Total Area:	8,048			68.0

Note: As shown above, each development block will need to achieve a higher water balance target to offset that of the new municipal right-of-way.

3400 Dufferin Street

Rational Method - 100 Year Storm

Mixed-Use Development

Block B (Building A)



$$I_{100\text{-year}} = \frac{59.7}{(10)^{0.80}} = 250.32 \text{ mm/hr}$$

Project Name:	3400 Dufferin Street	Controlled Area =	0.4046
Project Number:	139570	Weighed Runoff Coefficient =	0.77
Date:	28 July 2022	Orifice Discharge (L/s) =	26.2

Time (min)	Intensity (mm/hr)	Q-100 (L/s)	Q-stored (L/s)	Storage Volume (m ³)
0	0.0	0.000	0.000	0.000
10	250.3	215.897	189.712	113.827
20	143.8	124.001	97.815	117.378
30	103.9	89.650	63.465	114.237
40	82.6	71.220	45.034	108.082
50	69.1	59.576	33.391	100.172
60	59.7	51.490	25.305	91.099
70	52.8	45.517	19.331	81.191
80	47.4	40.905	14.720	70.655
90	43.2	37.227	11.041	59.624
100	39.7	34.217	8.032	48.193
110	36.8	31.705	5.520	36.433
120	34.3	29.573	3.388	24.396
130	32.2	27.739	1.554	12.120
140	30.3	26.142	0.000	0.000
150	28.7	24.739	0.000	0.000
160	27.2	23.494	0.000	0.000
170	25.9	22.381	0.000	0.000
180	24.8	21.381	0.000	0.000
190	23.7	20.476	0.000	0.000
200	22.8	19.653	0.000	0.000
210	21.9	18.900	0.000	0.000
220	21.1	18.210	0.000	0.000
230	20.4	17.574	0.000	0.000
240	19.7	16.986	0.000	0.000
250	19.1	16.440	0.000	0.000
260	18.5	15.932	0.000	0.000
270	17.9	15.458	0.000	0.000
280	17.4	15.015	0.000	0.000
290	16.9	14.599	0.000	0.000
300	16.5	14.209	0.000	0.000
310	16.0	13.841	0.000	0.000
320	15.6	13.494	0.000	0.000
330	15.3	13.165	0.000	0.000
340	14.9	12.855	0.000	0.000
350	14.6	12.560	0.000	0.000
360	14.2	12.280	0.000	0.000

Storage Volume Required (cu.m) =	117.4
Storage Volume Provided (cu.m) =	134.9
HGL Depth (m) =	1.8
Orifice Diameter (mm) =	95

3400 Dufferin Street

Mixed-Use Development



Water Quality Calculations

Block B (Building A)

Project Name: 3400 Dufferin Street

Project Number: 139570

Date: 28 July 2022

Designed By: Jason Jenkins, P.Eng.

TSS Removal (Un-Treated)

Surface	Area (m ²)		Effective TSS Removal	Overall TSS Removal
Conventional Roof	1,387	34.3%	80	27.4
Green Roof	1,088	26.9%	80	21.5
Landscape	0	0.0%	80	0.0
Landscape over P1	225	5.6%	80	4.4
Permeable Pavers	0	0.0%	80	0.0
Impervious	1,346	33.3%	0	0.0
Total Area:	4,046	100%		53.4

Treatment Required

TSS Removal (Treated)

Surface	Area (m ²)		Effective TSS Removal	Overall TSS Removal
0	1,387	34.3%	80	27.4
0	1,088	26.9%	80	21.5
0	0	0.0%	80	0.0
0	225	5.6%	80	4.4
0	0	0.0%	80	0.0
0	1,346	33.3%	80	26.6
Total Area:	4,046	100%		80.0

Site Meets 80% TSS Removal

3400 Dufferin Street

Mixed-Use Development

**Water Balance Calculations**

Block B (Building A)

Project Name: 3400 Dufferin Street

Project Number: 139570

Date: 28 July 2022

Designed By: Jason Jenkins, P.Eng.

Total Volume to be Retained	
Required Water Balance (mm):	7.0
Recall Site Area (m ²):	4,046
Total Water Balance to be Retained (m ³):	28.4

(Adjusted to offset road)

Volume Achieved Through Initial Abstraction				
Surface	Area (m ²)		I.A.	Vol. (m ³)
Conventional Roof	1,387		1	1.4
Green Roof	1,088		7	7.6
Landscape	0		5	0.0
Landscape over P1	225		5	1.1
Permeable Pavers	0		5	0.0
Impervious	1,346		1	1.3
Total Area:	4,046			11.5

Water Balance Summary		Vol. (m ³)
Recall Initial Abstraction (see above):		11.5
Water Re-Use (Irrigation):		16.9
Water Re-Use (Toilet Flushing):		
Total Water Balance Achieved:		28.4

Site Meets City's Water Balance Criteria

Check Tank Capacity to Capture Re-Use Volume	
Area of SWM Tank (m ²):	95.0
Float Switch Operating Range (m):	0.20
Total Water Balance Achieved:	19.0

SWM Tank has sufficient capacity for Re-Use Volumes

3400 Dufferin Street

Rational Method - 100 Year Storm

Mixed-Use Development

Block D (Building B)



$$I_{100\text{-year}} = \frac{59.7}{(10)^{0.80}} = 250.32 \text{ mm/hr}$$

Project Name:	3400 Dufferin Street	Controlled Area =		0.4002
Project Number:	139570	Weighed Runoff Coefficient =		0.73
Date:	28 July 2022	Orifice Discharge (L/s) =		23.3
Time (min)	Intensity (mm/hr)	Q-100 (L/s)	Q-stored (L/s)	Storage Volume (m ³)
0	0.0	0.000	0.000	0.000
10	250.3	204.042	180.701	108.421
20	143.8	117.191	93.851	112.621
30	103.9	84.727	61.387	110.496
40	82.6	67.309	43.968	105.524
50	69.1	56.305	32.964	98.892
60	59.7	48.663	25.322	91.161
70	52.8	43.017	19.677	82.642
80	47.4	38.659	15.318	73.527
90	43.2	35.182	11.842	63.946
100	39.7	32.338	8.998	53.988
110	36.8	29.964	6.624	43.717
120	34.3	27.950	4.609	33.185
130	32.2	26.216	2.875	22.428
140	30.3	24.707	1.366	11.477
150	28.7	23.380	0.040	0.356
160	27.2	22.204	0.000	0.000
170	25.9	21.152	0.000	0.000
180	24.8	20.207	0.000	0.000
190	23.7	19.352	0.000	0.000
200	22.8	18.574	0.000	0.000
210	21.9	17.863	0.000	0.000
220	21.1	17.210	0.000	0.000
230	20.4	16.609	0.000	0.000
240	19.7	16.053	0.000	0.000
250	19.1	15.537	0.000	0.000
260	18.5	15.057	0.000	0.000
270	17.9	14.609	0.000	0.000
280	17.4	14.190	0.000	0.000
290	16.9	13.798	0.000	0.000
300	16.5	13.428	0.000	0.000
310	16.0	13.081	0.000	0.000
320	15.6	12.753	0.000	0.000
330	15.3	12.443	0.000	0.000
340	14.9	12.149	0.000	0.000
350	14.6	11.870	0.000	0.000
360	14.2	11.606	0.000	0.000

Storage Volume Required (cu.m) =	112.6
Storage Volume Provided (cu.m) =	168.4
HGL Depth (m) =	1.4
Orifice Diameter (mm) =	95

3400 Dufferin Street

Mixed-Use Development

IBI

Water Quality Calculations

Block D (Building B)

Project Name: 3400 Dufferin Street

Project Number: 139570

Date: 28 July 2022

Designed By: Jason Jenkins, P.Eng.

TSS Removal (Un-Treated)

Surface	Area (m ²)		Effective TSS Removal	Overall TSS Removal
Conventional Roof	1,399	35.0%	80	28.0
Intensive Green Roof	1,026	25.6%	80	20.5
Landscape	0	0.0%	80	0.0
Landscape over P1	571	14.3%	80	11.4
Permeable Pavers	0	0.0%	80	0.0
Impervious	1,006	25.1%	0	0.0
Total Area:	4,002	100%		59.9

Treatment Required

TSS Removal (Treated)

Surface	Area (m ²)		Effective TSS Removal	Overall TSS Removal
Permeable Pavers	1,399	35.0%	80	28.0
Impervious	1,026	25.6%	80	20.5
Total Area	0	0.0%	80	0.0
0	571	14.3%	80	11.4
Block D (Towers X an	0	0.0%	80	0.0
Conventional Roof	1,006	25.1%	80	20.1
Total Area:	4,002	100%		80.0

Site Meets 80% TSS Removal

3400 Dufferin Street

Mixed-Use Development

**Water Balance Calculations**

Block D (Building B)

Project Name: 3400 Dufferin Street

Project Number: 139570

Date: 28 July 2022

Designed By: Jason Jenkins, P.Eng.

Total Volume to be Retained	
Required Water Balance (mm):	7.0
Recall Site Area (m ²):	4,002
Total Water Balance to be Retained (m ³):	28.0

(Adjusted to offset road)

Volume Achieved Through Initial Abstraction				
Surface	Area (m ²)		I.A.	Vol. (m ³)
Conventional Roof	1,399		1	1.4
Green Roof	1,026		7	7.2
Landscape	0		5	0.0
Landscape over P1	571		5	2.9
Permeable Pavers	0		5	0.0
Impervious	1,006		1	1.0
Total Area:	4,002			12.4

Water Balance Summary		Vol. (m ³)
Recall Initial Abstraction (see above):		12.4
Water Re-Use (Irrigation):		15.6
Water Re-Use (Toilet Flushing):		
Total Water Balance Achieved:		28.0

DOES NOT WORK

Check Tank Capacity to Capture Re-Use Volume	
Area of SWM Tank (m ²):	87.0
Float Switch Operating Range (m):	0.20
Total Water Balance Achieved:	17.4

SWM Tank has sufficient capacity for Re-Use Volumes

3400 Dufferin Street

Rational Method - 100 Year Storm

Mixed-Use Development

Block E (Building C)



$$I_{100\text{-year}} = \frac{59.7}{(10)^{0.80}} = 250.32 \text{ mm/hr}$$

Project Name:	3400 Dufferin Street	Controlled Area =		0.1652
Project Number:	139570	Weighed Runoff Coefficient =		0.76
Date:	28 July 2022	Orifice Discharge (L/s) =		11.3
Time (min)	Intensity (mm/hr)	Q-100 (L/s)	Q-stored (L/s)	Storage Volume (m ³)
0	0.0	0.000	0.000	0.000
10	250.3	87.588	76.255	45.753
20	143.8	50.306	38.974	46.768
30	103.9	36.370	25.038	45.069
40	82.6	28.893	17.561	42.146
50	69.1	24.169	12.837	38.512
60	59.7	20.889	9.557	34.405
70	52.8	18.466	7.134	29.961
80	47.4	16.595	5.263	25.261
90	43.2	15.102	3.770	20.360
100	39.7	13.882	2.550	15.297
110	36.8	12.863	1.530	10.101
120	34.3	11.998	0.666	4.792
130	32.2	11.254	0.000	0.000
140	30.3	10.606	0.000	0.000
150	28.7	10.036	0.000	0.000
160	27.2	9.531	0.000	0.000
170	25.9	9.080	0.000	0.000
180	24.8	8.674	0.000	0.000
190	23.7	8.307	0.000	0.000
200	22.8	7.973	0.000	0.000
210	21.9	7.668	0.000	0.000
220	21.1	7.388	0.000	0.000
230	20.4	7.130	0.000	0.000
240	19.7	6.891	0.000	0.000
250	19.1	6.669	0.000	0.000
260	18.5	6.463	0.000	0.000
270	17.9	6.271	0.000	0.000
280	17.4	6.091	0.000	0.000
290	16.9	5.923	0.000	0.000
300	16.5	5.764	0.000	0.000
310	16.0	5.615	0.000	0.000
320	15.6	5.474	0.000	0.000
330	15.3	5.341	0.000	0.000
340	14.9	5.215	0.000	0.000
350	14.6	5.096	0.000	0.000
360	14.2	4.982	0.000	0.000

Storage Volume Required (cu.m) =	46.8
Storage Volume Provided (cu.m) =	105.4
HGL Depth (m) =	0.9
Orifice Diameter (mm) =	75

3400 Dufferin Street

Mixed-Use Development

IBI

Water Quality Calculations

Block E (Building C)

Project Name: 3400 Dufferin Street

Project Number: 139570

Date: 28 July 2022

Designed By: Jason Jenkins, P.Eng.

TSS Removal (Un-Treated)

Surface	Area (m ²)		Effective TSS Removal	Overall TSS Removal
Conventional Roof	672	40.7%	80	32.5
Intensive Green Roof	362	21.9%	80	17.5
Landscape	0	0.0%	80	0.0
Landscape over P1	183	11.1%	80	8.9
Permeable Pavers	0	0.0%	80	0.0
Impervious	435	26.3%	0	0.0
Total Area:	1,652	100%		58.9

Treatment Required

TSS Removal (Treated)

Surface	Area (m ²)		Effective TSS Removal	Overall TSS Removal
Permeable Pavers	672	40.7%	80	32.5
Impervious	362	21.9%	80	17.5
Total Area	0	0.0%	80	0.0
0	183	11.1%	80	8.9
Block D (Towers X an	0	0.0%	80	0.0
Conventional Roof	435	26.3%	80	21.1
Total Area:	1,652	100%		80.0

Site Meets 80% TSS Removal

3400 Dufferin Street

Mixed-Use Development

**Water Balance Calculations**

Block E (Building C)

Project Name: 3400 Dufferin Street

Project Number: 139570

Date: 28 July 2022

Designed By: Jason Jenkins, P.Eng.

Total Volume to be Retained	
Required Water Balance (mm):	7.0
Recall Site Area (m ²):	1,652
Total Water Balance to be Retained (m ³):	11.6

(Adjusted to offset road)

Volume Achieved Through Initial Abstraction				
Surface	Area (m ²)		I.A.	Vol. (m ³)
Conventional Roof	672		1	0.7
Green Roof	362		7	2.5
Landscape	0		5	0.0
Landscape over P1	183		5	0.9
Permeable Pavers	0		5	0.0
Impervious	435		1	0.4
Total Area:	1,652			4.6

Water Balance Summary		Vol. (m ³)
Recall Initial Abstraction (see above):		4.6
Water Re-Use (Irrigation):		7.0
Water Re-Use (Toilet Flushing):		
Total Water Balance Achieved:		11.6

DOES NOT WORK

Check Tank Capacity to Capture Re-Use Volume	
Area of SWM Tank (m ²):	53.0
Float Switch Operating Range (m):	0.20
Total Water Balance Achieved:	10.6

SWM Tank has sufficient capacity for Re-Use Volumes

Municipal Right-of-Way



CDS AVERAGE ANNUAL EFFICIENCY FOR TSS REMOVAL & TOTAL ANNUAL VOLUME TREATED



Project: 3400 Dufferin St
Location: Toronto
OGS ID: OGS4 (Municipal Rd)

Engineer: IBI Group
Contact: Shirley Beaudoin
Date: 7/Jul/22

Area: 0.82 ha
Rc: 0.64
Upstream Storage: 195.6 m3
CDS Model: CDS-5

Treatment Capacity: 42 l/s
Particle Size Distribution: City of Toronto
IDF Rainfall Data: City of Toronto

Return	Period	Peak Flow	TSS Percentage Captured	Treated Flow Volume	Total Flow Volume	Annual Exceedance Probability	System Flow	CDS Flow	By-Pass Flow	Volume Percentage Treated
month / yr	Yr	l/s	%	litres	litres	%	l/s	l/s	l/s	%
1-M	0.083	2.54	93.20	2116	2116	100.00	2.54	2.54	0.00	100.00
2-M	0.1667	9.46	90.69	7990	7990	99.75	9.46	9.46	0.00	100.00
3-M	0.25	14.99	88.74	12744	12744	98.17	14.99	14.99	0.00	100.00
4-M	0.333	20.00	86.97	17086	17086	95.04	20.00	20.00	0.00	100.00
5-M	0.417	28.14	84.02	24534	24534	90.91	28.14	28.14	0.00	100.00
6-M	0.5	36.28	81.07	31982	31982	86.47	36.28	36.28	0.00	100.00
7-M	0.583	38.42	80.28	33998	34004	82.01	38.42	38.42	0.00	99.98
8-M	0.667	40.57	79.49	36015	36027	77.67	40.57	40.57	0.00	99.97
9-M	0.75	42.71	78.71	38032	38049	73.64	42.71	42.48	0.23	99.95
10-M	0.833	46.71	76.35	40818	41873	69.90	46.71	42.48	4.24	97.86
11-M	0.917	50.71	73.99	43605	45697	66.40	50.71	42.48	8.24	95.77
1-Yr	1	54.72	71.63	46392	49521	63.21	54.72	42.48	12.24	93.68
2-Yr	2	60.90	67.70	49599	55533	39.35	60.90	42.48	18.42	89.32
5-Yr	5	74.27	60.06	55274	68875	18.13	74.27	42.48	31.79	80.25
10-Yr	10	84.46	55.00	58567	79148	9.52	84.46	42.48	41.98	74.00
25-Yr	25	96.50	49.84	61709	91445	3.92	96.50	42.48	54.03	67.48
50-Yr	50	108.88	45.32	64423	104522	1.98	108.88	42.48	66.40	61.64
100-Yr	100	121.90	41.30	66990	118869	1.00	121.90	42.48	79.42	56.36


Average Annual TSS Removal Efficiency [%]: **80.3** Ave. Ann. T. Volume [%]: **97.9**

Notes:

- 1) CDS Efficiency based on testing conducted at the University of Central Florida
- 2) CDS design flowrate and scaling based on standard manufacturer model & product specifications


CDS-5-C DESIGN NOTES

THE STANDARD CDS-5-C CONFIGURATION IS SHOWN.




PLAN VIEW B-B

N.T.S.



ELEVATION A-A

N.T.S.



FRAME AND COVER

(DIAMETER VARIES)

N.T.S.

SITE SPECIFIC DATA REQUIREMENTS

STRUCTURE ID				*
WATER QUALITY FLOW RATE (CFS OR L/s)				*
PEAK FLOW RATE (CFS OR L/s)				*
RETURN PERIOD OF PEAK FLOW (YRS)				*
SCREEN APERTURE (2400 OR 4700)				*
PIPE DATA:	I.E.	MATERIAL	DIAMETER	
INLET PIPE 1	*	*	*	
INLET PIPE 2	*	*	*	
OUTLET PIPE	*	*	*	

RIM ELEVATION			*
ANTI-FLOTATION BALLAST	WIDTH	HEIGHT	
	*	*	

NOTES/SPECIAL REQUIREMENTS:

* PER ENGINEER OF RECORD

GENERAL NOTES

1. CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
2. DIMENSIONS MARKED WITH () ARE REFERENCE DIMENSIONS. ACTUAL DIMENSIONS MAY VARY.
3. FOR FABRICATION DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHTS, PLEASE CONTACT YOUR CONTECH ENGINEERED SOLUTIONS LLC REPRESENTATIVE. www.ContechES.com
4. CDS WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING.
5. STRUCTURE SHALL MEET AASHTO HS20 LOAD RATING, ASSUMING GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET HS20 (AASHTO M 306) AND BE CAST WITH THE CONTECH LOGO.
6. IF REQUIRED, PVC HYDRAULIC SHEAR PLATE IS PLACED ON SHELF AT BOTTOM OF SCREEN CYLINDER. REMOVE AND REPLACE AS NECESSARY DURING MAINTENANCE CLEANING.

INSTALLATION NOTES

- A. ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
- B. CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE CDS MANHOLE STRUCTURE (LIFTING CLUTCHES PROVIDED).
- C. CONTRACTOR TO ADD JOINT SEALANT BETWEEN ALL STRUCTURE SECTIONS, AND ASSEMBLE STRUCTURE.
- D. CONTRACTOR TO PROVIDE, INSTALL, AND GROUT PIPES. MATCH PIPE INVERTS WITH ELEVATIONS SHOWN.
- E. CONTRACTOR TO TAKE APPROPRIATE MEASURES TO ASSURE UNIT IS WATER TIGHT, HOLDING WATER TO FLOWLINE INVERT MINIMUM. IT IS SUGGESTED THAT ALL JOINTS BELOW PIPE INVERTS ARE GROUTED.



THIS PRODUCT MAY BE PROTECTED BY ONE OR MORE OF THE FOLLOWING U.S. PATENTS: 5,786,886; 6,641,720; 6,517,080; 6,581,782; RELATED FOREIGN PATENTS, OR OTHER PATENTS PENDING.



www.ContechES.com

9025 Centre Pointe Dr., Suite 400, West Chester, OH 45069

800-338-1122 513-645-7000 513-645-7993 FAX

CDS-5-C
ONLINE CDS
STANDARD DETAIL



Determining Number of Cartridges for Flow Based Systems

Date

7/7/2022

Black Cells = Calculation

Site Information

Project Name	3400 Dufferin St	
Project Location	Toronto, ON	
OGS ID	OGS1 (Block B)	
Drainage Area, Ad	0.14 ac	(0.0569 ha)
Impervious Area, Ai	0.14 ac	
Pervious Area, Ap	0.00	
% Impervious	100%	
Runoff Coefficient, Rc	0.90	
Treatment storm flow rate, Q_{treat}	0.10 cfs	(2.8 L/s)
Peak storm flow rate, Q_{peak}	1.26 cfs	(35.6 L/s)

Filter System

Filtration brand	StormFilter	
Cartridge height	12 in	
Specific Flow Rate	2.00 gpm/ft ²	
Flow rate per cartridge	10.00 gpm	



SUMMARY

Number of Cartridges	5
Media Type	Perlite

Event Mean Concentration (EMC)	150 mg/L
Annual TSS Removal	80%
Percent Runoff Capture	90%

Recommend SFPD0608 vault or CIP

I:\COMMON\CAD\TREATMENT\10 STORMFILTER\40 STANDARD DRAWINGS\SPD\STANDARDIN PROCESS\DWG\SFPD0608-DTL.DWG 10/20/2020 3:06 PM




STORMFILTER DESIGN NOTES


- STORMFILTER TREATMENT CAPACITY VARIES BY CARTRIDGE COUNT AND LOCALLY APPROVED SURFACE AREA SPECIFIC FLOW RATE. PEAK CONVEYANCE CAPACITY TO BE DETERMINED BY ENGINEER OF RECORD
- A 6' x 8' [1829 x 2438] PEAK DIVERSION STYLE STORMFILTER IS SHOWN WITH THE MAXIMUM NUMBER OF CARTRIDGES (8) AND IS AVAILABLE IN A LEFT INLET (AS SHOWN) OR A RIGHT INLET CONFIGURATION
- ALL PARTS AND INTERNAL ASSEMBLY PROVIDED BY CONTECH UNLESS NOTED OTHERWISE

CARTRIDGE SIZE (in. [mm])	27 [686]			18 [457]			LOW DROP		
RECOMMENDED HYDRAULIC DROP (H) (ft. [mm])	3.05 [930]			2.3 [701]			1.8 [549]		
HEIGHT OF WEIR (W) (ft. [mm])	3.00 [914]			2.25 [686]			1.75 [533]		
SPECIFIC FLOW RATE (gpm/sf [L/s/m ²])	2 [1.36]	1.67* [1.13]*	1 [0.68]	2 [1.36]	1.67* [1.13]*	1 [0.68]	2 [1.36]	1.67* [1.13]*	1 [0.68]
CARTRIDGE FLOW RATE (gpm [L/s])	22.5 [1.42]	18.79 [1.19]	11.25 [0.71]	15 [0.95]	12.53 [0.79]	7.5 [0.47]	10 [0.63]	8.35 [0.53]	5 [0.32]

* 1.67 gpm/sf [1.13 L/s/m²] SPECIFIC FLOW RATE IS APPROVED WITH PHOSPHOSORB® (PSORB) MEDIA ONLY



FRAME AND GRATE
(24" SQUARE)
(NOT TO SCALE)



FRAME AND COVER
(30" ROUND)
(NOT TO SCALE)

SITE SPECIFIC DATA REQUIREMENTS

STRUCTURE ID	
WATER QUALITY FLOW RATE (cfs [L/s])	
PEAK FLOW RATE (cfs [L/s])	
RETURN PERIOD OF PEAK FLOW (yrs)	
CARTRIDGE FLOW RATE	
CARTRIDGE SIZE (27, 18, LOW DROP (LD))	
MEDIA TYPE (PERLITE, ZPG, PSORB)	
NUMBER OF CARTRIDGES REQUIRED	
INLET BAY RIM ELEVATION	
FILTER BAY RIM ELEVATION	
PIPE DATA:	INVERT MATERIAL DIAMETER
INLET PIPE 1	
INLET PIPE 2	
OUTLET PIPE	

NOTES/SPECIAL REQUIREMENTS:

PERFORMANCE SPECIFICATION

FILTER CARTRIDGES SHALL BE MEDIA-FILLED, PASSIVE, SIPHON ACTUATED, RADIAL FLOW, AND SELF CLEANING. **RADIAL MEDIA DEPTH SHALL BE 7" [178]**. FILTER MEDIA CONTACT TIME SHALL BE AT LEAST **37 SECONDS**. SPECIFIC FLOW RATE SHALL BE **2 GPM/SF [1.36 L/s/m²] (MAXIMUM)**. SPECIFIC FLOW RATE IS THE MEASURE OF THE FLOW (GPM) DIVIDED BY THE MEDIA SURFACE CONTACT AREA (SF). MEDIA VOLUMETRIC FLOW RATE SHALL BE **6 GPM/CF [13.39 L/s/m³] OF MEDIA (MAXIMUM)**.

GENERAL NOTES

1. CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
2. DIMENSIONS MARKED WITH () ARE REFERENCE DIMENSIONS. ACTUAL DIMENSIONS MAY VARY.
3. ALTERNATE DIMENSIONS ARE IN MILLIMETERS [mm] UNLESS NOTED OTHERWISE.
4. FOR FABRICATION DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHTS, PLEASE CONTACT YOUR CONTECH REPRESENTATIVE. www.ContechES.com
5. STORMFILTER WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
6. STRUCTURE SHALL MEET AASHTO HS20 LOAD RATING, ASSUMING EARTH COVER OF 0' - 10' [3048] AND GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 AND BE CAST WITH THE CONTECH LOGO.

INSTALLATION NOTES

- A. ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
- B. CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE STORMFILTER STRUCTURE.
- C. CONTRACTOR TO INSTALL JOINT SEALANT BETWEEN ALL SECTIONS AND ASSEMBLE STRUCTURE.
- D. CONTRACTOR TO PROVIDE, INSTALL, AND GROUT PIPES. MATCH OUTLET PIPE INVERT WITH OUTLET BAY FLOOR.
- E. CONTRACTOR TO TAKE APPROPRIATE MEASURES TO PROTECT CARTRIDGES FROM CONSTRUCTION-RELATED EROSION RUNOFF.
- F. CONTRACTOR TO REMOVE THE TRANSFER OPENING COVER WHEN THE SYSTEM IS BROUGHT ONLINE.



THIS PRODUCT MAY BE PROTECTED BY ONE OR MORE OF THE FOLLOWING
U.S. PATENTS: 5,322,629; 5,524,576; 5,707,527; 5,985,157; 6,027,639; 6,649,048;
RELATED FOREIGN PATENTS, OR OTHER PATENTS PENDING.



www.ContechES.com
9025 Centre Pointe Dr., Suite 400, West Chester, OH 45069
800-338-1122 513-645-7000 513-645-7993 FAX

SFPD0608 (6' x 8')
PEAK DIVERSION STORMFILTER
STANDARD DETAIL



Determining Number of Cartridges for Flow Based Systems

Date

7/7/2022

Black Cells = Calculation

Site Information

Project Name	3400 Dufferin St	
Project Location	Toronto, ON	
OGS ID	OGS2 (Block D)	
Drainage Area, Ad	0.11 ac	(0.0463 ha)
Impervious Area, Ai	0.11 ac	
Pervious Area, Ap	0.00	
% Impervious	100%	
Runoff Coefficient, Rc	0.90	
Treatment storm flow rate, Q_{treat}	0.08 cfs	(2.3 L/s)
Peak storm flow rate, Q_{peak}	1.02 cfs	(29 L/s)

Filter System

Filtration brand	StormFilter	
Cartridge height	12 in	
Specific Flow Rate	2.00 gpm/ft ²	
Flow rate per cartridge	10.00 gpm	

SUMMARY

Number of Cartridges	4
Media Type	Perlite

Event Mean Concentration (EMC)	150 mg/L
Annual TSS Removal	80%
Percent Runoff Capture	90%

Recommend SFPD0608 vault or CIP




I:\COMMON\CAD\TREATMENT\10 STORMFILTER\40 STANDARD DRAWINGS\SFPD\STANDARDIN PROCESS\DWG\SFPD0608-DTL.DWG 10/20/2020 3:06 PM

STORMFILTER DESIGN NOTES


- STORMFILTER TREATMENT CAPACITY VARIES BY CARTRIDGE COUNT AND LOCALLY APPROVED SURFACE AREA SPECIFIC FLOW RATE. PEAK CONVEYANCE CAPACITY TO BE DETERMINED BY ENGINEER OF RECORD
- A 6' x 8' [1829 x 2438] PEAK DIVERSION STYLE STORMFILTER IS SHOWN WITH THE MAXIMUM NUMBER OF CARTRIDGES (8) AND IS AVAILABLE IN A LEFT INLET (AS SHOWN) OR A RIGHT INLET CONFIGURATION
- ALL PARTS AND INTERNAL ASSEMBLY PROVIDED BY CONTECH UNLESS NOTED OTHERWISE

CARTRIDGE SIZE (in. [mm])	27 [686]			18 [457]			LOW DROP		
RECOMMENDED HYDRAULIC DROP (H) (ft. [mm])	3.05 [930]			2.3 [701]			1.8 [549]		
HEIGHT OF WEIR (W) (ft. [mm])	3.00 [914]			2.25 [686]			1.75 [533]		
SPECIFIC FLOW RATE (gpm/sf [L/s/m ²])	2 [1.36]	1.67* [1.13]*	1 [0.68]	2 [1.36]	1.67* [1.13]*	1 [0.68]	2 [1.36]	1.67* [1.13]*	1 [0.68]
CARTRIDGE FLOW RATE (gpm [L/s])	22.5 [1.42]	18.79 [1.19]	11.25 [0.71]	15 [0.95]	12.53 [0.79]	7.5 [0.47]	10 [0.63]	8.35 [0.53]	5 [0.32]

* 1.67 gpm/sf [1.13 L/s/m²] SPECIFIC FLOW RATE IS APPROVED WITH PHOSPHOSORB® (PSORB) MEDIA ONLY



FRAME AND GRATE
(24" SQUARE)
(NOT TO SCALE)



FRAME AND COVER
(30" ROUND)
(NOT TO SCALE)

SITE SPECIFIC DATA REQUIREMENTS

STRUCTURE ID	
WATER QUALITY FLOW RATE (cfs [L/s])	
PEAK FLOW RATE (cfs [L/s])	
RETURN PERIOD OF PEAK FLOW (yrs)	
CARTRIDGE FLOW RATE	
CARTRIDGE SIZE (27, 18, LOW DROP (LD))	
MEDIA TYPE (PERLITE, ZPG, PSORB)	
NUMBER OF CARTRIDGES REQUIRED	
INLET BAY RIM ELEVATION	
FILTER BAY RIM ELEVATION	
PIPE DATA:	INVERT MATERIAL DIAMETER
INLET PIPE 1	
INLET PIPE 2	
OUTLET PIPE	
NOTES/SPECIAL REQUIREMENTS:	

PERFORMANCE SPECIFICATION

FILTER CARTRIDGES SHALL BE MEDIA-FILLED, PASSIVE, SIPHON ACTUATED, RADIAL FLOW, AND SELF CLEANING. **RADIAL MEDIA DEPTH SHALL BE 7" [178]**. FILTER MEDIA CONTACT TIME SHALL BE AT LEAST **37 SECONDS**. SPECIFIC FLOW RATE SHALL BE **2 GPM/SF [1.36 L/s/m²] (MAXIMUM)**. SPECIFIC FLOW RATE IS THE MEASURE OF THE FLOW (GPM) DIVIDED BY THE MEDIA SURFACE CONTACT AREA (SF). MEDIA VOLUMETRIC FLOW RATE SHALL BE **6 GPM/CF [13.39 L/s/m³] OF MEDIA (MAXIMUM)**.

GENERAL NOTES

1. CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
2. DIMENSIONS MARKED WITH () ARE REFERENCE DIMENSIONS. ACTUAL DIMENSIONS MAY VARY.
3. ALTERNATE DIMENSIONS ARE IN MILLIMETERS [mm] UNLESS NOTED OTHERWISE.
4. FOR FABRICATION DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHTS, PLEASE CONTACT YOUR CONTECH REPRESENTATIVE. www.ContechES.com
5. STORMFILTER WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
6. STRUCTURE SHALL MEET AASHTO HS20 LOAD RATING, ASSUMING EARTH COVER OF 0' - 10' [3048] AND GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 AND BE CAST WITH THE CONTECH LOGO.

INSTALLATION NOTES

- A. ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
- B. CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE STORMFILTER STRUCTURE.
- C. CONTRACTOR TO INSTALL JOINT SEALANT BETWEEN ALL SECTIONS AND ASSEMBLE STRUCTURE.
- D. CONTRACTOR TO PROVIDE, INSTALL, AND GROUT PIPES. MATCH OUTLET PIPE INVERT WITH OUTLET BAY FLOOR.
- E. CONTRACTOR TO TAKE APPROPRIATE MEASURES TO PROTECT CARTRIDGES FROM CONSTRUCTION-RELATED EROSION RUNOFF.
- F. CONTRACTOR TO REMOVE THE TRANSFER OPENING COVER WHEN THE SYSTEM IS BROUGHT ONLINE.



THIS PRODUCT MAY BE PROTECTED BY ONE OR MORE OF THE FOLLOWING
U.S. PATENTS: 5,322,629; 5,524,576; 5,707,527; 5,985,157; 6,027,639; 6,649,048;
RELATED FOREIGN PATENTS, OR OTHER PATENTS PENDING.



www.ContechES.com
9025 Centre Pointe Dr., Suite 400, West Chester, OH 45069
800-338-1122 513-645-7000 513-645-7993 FAX

SFPD0608 (6' x 8')
PEAK DIVERSION STORMFILTER
STANDARD DETAIL



Determining Number of Cartridges for Flow Based Systems

Date

7/7/2022

Black Cells = Calculation

Site Information

Project Name	3400 Dufferin St	
Project Location	Toronto, ON	
OGS ID	OGS3 (Block E)	
Drainage Area, Ad	0.06 ac	(0.0234 ha)
Impervious Area, Ai	0.06 ac	
Pervious Area, Ap	0.00	
% Impervious	100%	
Runoff Coefficient, Rc	0.90	
Treatment storm flow rate, Q_{treat}	0.04 cfs	(1.2 L/s)
Peak storm flow rate, Q_{peak}	0.52 cfs	(14.6 L/s)

Filter System

Filtration brand	StormFilter	
Cartridge height	12 in	
Specific Flow Rate	2.00 gpm/ft ²	
Flow rate per cartridge	10.00 gpm	

SUMMARY

Number of Cartridges	2
Media Type	Perlite

Event Mean Concentration (EMC)	150 mg/L
Annual TSS Removal	80%
Percent Runoff Capture	90%

Recommend SFPD0608 vault or CIP




I:\COMMON\CAD\TREATMENT\10 STORMFILTER\40 STANDARD DRAWINGS\SPD\STANDARDIN PROCESS\DWG\SFPD0608-DTL.DWG 10/20/2020 3:06 PM

STORMFILTER DESIGN NOTES


- STORMFILTER TREATMENT CAPACITY VARIES BY CARTRIDGE COUNT AND LOCALLY APPROVED SURFACE AREA SPECIFIC FLOW RATE. PEAK CONVEYANCE CAPACITY TO BE DETERMINED BY ENGINEER OF RECORD
- A 6' x 8' [1829 x 2438] PEAK DIVERSION STYLE STORMFILTER IS SHOWN WITH THE MAXIMUM NUMBER OF CARTRIDGES (8) AND IS AVAILABLE IN A LEFT INLET (AS SHOWN) OR A RIGHT INLET CONFIGURATION
- ALL PARTS AND INTERNAL ASSEMBLY PROVIDED BY CONTECH UNLESS NOTED OTHERWISE

CARTRIDGE SIZE (in. [mm])	27 [686]			18 [457]			LOW DROP		
RECOMMENDED HYDRAULIC DROP (H) (ft. [mm])	3.05 [930]			2.3 [701]			1.8 [549]		
HEIGHT OF WEIR (W) (ft. [mm])	3.00 [914]			2.25 [686]			1.75 [533]		
SPECIFIC FLOW RATE (gpm/sf [L/s/m ²])	2 [1.36]	1.67* [1.13]*	1 [0.68]	2 [1.36]	1.67* [1.13]*	1 [0.68]	2 [1.36]	1.67* [1.13]*	1 [0.68]
CARTRIDGE FLOW RATE (gpm [L/s])	22.5 [1.42]	18.79 [1.19]	11.25 [0.71]	15 [0.95]	12.53 [0.79]	7.5 [0.47]	10 [0.63]	8.35 [0.53]	5 [0.32]

* 1.67 gpm/sf [1.13 L/s/m²] SPECIFIC FLOW RATE IS APPROVED WITH PHOSPHOSORB® (PSORB) MEDIA ONLY



FRAME AND GRATE
(24" SQUARE)
(NOT TO SCALE)



FRAME AND COVER
(30" ROUND)
(NOT TO SCALE)

SITE SPECIFIC DATA REQUIREMENTS

STRUCTURE ID	
WATER QUALITY FLOW RATE (cfs [L/s])	
PEAK FLOW RATE (cfs [L/s])	
RETURN PERIOD OF PEAK FLOW (yrs)	
CARTRIDGE FLOW RATE	
CARTRIDGE SIZE (27, 18, LOW DROP (LD))	
MEDIA TYPE (PERLITE, ZPG, PSORB)	
NUMBER OF CARTRIDGES REQUIRED	
INLET BAY RIM ELEVATION	
FILTER BAY RIM ELEVATION	
PIPE DATA:	INVERT MATERIAL DIAMETER
INLET PIPE 1	
INLET PIPE 2	
OUTLET PIPE	
NOTES/SPECIAL REQUIREMENTS:	

PERFORMANCE SPECIFICATION

FILTER CARTRIDGES SHALL BE MEDIA-FILLED, PASSIVE, SIPHON ACTUATED, RADIAL FLOW, AND SELF CLEANING. **RADIAL MEDIA DEPTH SHALL BE 7" [178]**. FILTER MEDIA CONTACT TIME SHALL BE AT LEAST **37 SECONDS**. SPECIFIC FLOW RATE SHALL BE **2 GPM/SF [1.36 L/s/m²] (MAXIMUM)**. SPECIFIC FLOW RATE IS THE MEASURE OF THE FLOW (GPM) DIVIDED BY THE MEDIA SURFACE CONTACT AREA (SF). MEDIA VOLUMETRIC FLOW RATE SHALL BE **6 GPM/CF [13.39 L/s/m³] OF MEDIA (MAXIMUM)**.

GENERAL NOTES

1. CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
2. DIMENSIONS MARKED WITH () ARE REFERENCE DIMENSIONS. ACTUAL DIMENSIONS MAY VARY.
3. ALTERNATE DIMENSIONS ARE IN MILLIMETERS [mm] UNLESS NOTED OTHERWISE.
4. FOR FABRICATION DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHTS, PLEASE CONTACT YOUR CONTECH REPRESENTATIVE. www.ContechES.com
5. STORMFILTER WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
6. STRUCTURE SHALL MEET AASHTO HS20 LOAD RATING, ASSUMING EARTH COVER OF 0' - 10' [3048] AND GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 AND BE CAST WITH THE CONTECH LOGO.

INSTALLATION NOTES

- A. ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
- B. CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE STORMFILTER STRUCTURE.
- C. CONTRACTOR TO INSTALL JOINT SEALANT BETWEEN ALL SECTIONS AND ASSEMBLE STRUCTURE.
- D. CONTRACTOR TO PROVIDE, INSTALL, AND GROUT PIPES. MATCH OUTLET PIPE INVERT WITH OUTLET BAY FLOOR.
- E. CONTRACTOR TO TAKE APPROPRIATE MEASURES TO PROTECT CARTRIDGES FROM CONSTRUCTION-RELATED EROSION RUNOFF.
- F. CONTRACTOR TO REMOVE THE TRANSFER OPENING COVER WHEN THE SYSTEM IS BROUGHT ONLINE.



THIS PRODUCT MAY BE PROTECTED BY ONE OR MORE OF THE FOLLOWING
U.S. PATENTS: 5,322,629; 5,524,576; 5,707,527; 5,985,157; 6,027,639; 6,649,048;
RELATED FOREIGN PATENTS, OR OTHER PATENTS PENDING.



www.ContechES.com
9025 Centre Pointe Dr., Suite 400, West Chester, OH 45069
800-338-1122 513-645-7000 513-645-7993 FAX

SFPD0608 (6' x 8')
PEAK DIVERSION STORMFILTER
STANDARD DETAIL

Appendix C

Engineering Drawings

Site Plan Application Set

Draft Plan of Subdivision Set